



	KARTA WLAN USB ARCHER-T2U 150 Mb/s @ 2.4 GHz, 433 Mb/s @ 5 GHz TP-LINK	UCHWYT DO TELEWIZORA LUB MONITORA BRATECK- LP42-69T
		
	15.09 EUR 18.56 EUR	20.53 EUR 25.25 EUR
Obsługiwane standardy	IEEE 802.11 b/g/n @ 2.4 GHz, IEEE 802.11 a/n/ac @ 5 GHz	...
Chipset radiowy	Atheros	...
Obsługiwane prędkości	150 Mb/s @ 2.4 GHz , 433 Mb/s @ 5 GHz	...
Tryby pracy	Ad-Hoc, Infrastructure	...
Standard mocowania	...	VESA 75, 100, 150, 200, 200x100, 300, 400x200 400x300, 400, 600x400, 600, 800x600, 900x600
Rozmiar TV w calach	...	60 " ... 100 "
Modulacja	DBPSK / DQPSK / CCK / OFDM / 16-QAM / 64-QAM	...
Nośność	...	75 kg
Typ anteny	Wewnętrzna	...
Dystans od powierzchni montażu	...	85 mm
Interfejs	USB	...
Kolor	...	Czarny
Zakres częstotliwości	• 2.4 GHz • 5 GHz	...
Pochylenie w pionie	...	-10 ° ... 5 °

Czułość odbiornika	5 GHz • 11a 6M : -94 dBm • 11a 54M : -78 dBm • 11n HT20 MCS0 : -94 dBm • 11n HT20 MCS7 : -77 dBm • 11n HT40 MCS0 : -92 dBm • 11n HT40 MCS7 : -74 dBm • 11ac VHT80 MCS0 : -89 dBm • 11ac VHT80 MCS9 : -64 dBm 2.4 GHz • 11b 1M : -99 dBm • 11b 11M : -91 dBm • 11g 6M : -94 dBm • 11g 54M : -77 dBm • 11n HT20 MCS0 : -95 dBm • 11n HT20 MCS7 : -76 dBm • 11n HT40 MCS0 : -92 dBm • 11n HT40 MCS7 : -73 dBm	...
Bezpieczeństwo połączenia	WEP 64/128-bit, WPA-PSK/WPA2-PSK, 802.1x Radius	...
Dołączone sterowniki	Windows, Mac OS X, Linux	...
Certyfikaty	FCC, CE, RoHS	...
Temperatura pracy	0 °C ... 40 °C	...
Waga	0.006 kg	3.7 kg
Wymiary	41 x 20 x 9 mm	954 x 625 x 85 mm
Producent / Marka	TP-LINK	...
Gwarancja	3 lata	2 lata