



	<a href="#">NVR TC-R31640 SPEC:E/B/N/V4.0 40 CHANNELS TIANDY</a>	<a href="#">FLUSH BOX INSTALL-BOX/95X95/EPN Elektro-Plast</a>
		
	18789.00 PLN 18789.00 PLN	12.70 PLN 12.70 PLN
Standard	IP	...
Number of sections	...	1
Supported resolutions	max. 16 Mpx	...
"Index of Protection"	...	—
Video outputs	2 pcs HDMI 4K 2 pcs VGA Video outputs are independent of each other	...
Audio support	Audio from cameras	...
Audio inputs	1 pcs	...
Audio outputs	1 pcs	...
Main features	...	<ul style="list-style-type: none"> <li>• Flush-mounted, for hollow walls</li> <li>• Cover mounting with screws</li> <li>• 4 Mounting screws, 4 special screws with holders to fastening to the wall - included</li> </ul>
Material	...	Plastic
Image compression method	S+265 / H.265 / S+264 / H.264	...
Color	...	Brick red + White
Supported hard drives	16 x 18 TB SATA + 1 x eSATA	...
Recording modes	Manual, Motion Detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	<ul style="list-style-type: none"> <li>• Records searching: by time and events type. Records playback: forward, backward, fast, slow</li> <li>• Advanced searching (to the one second accuracy)</li> <li>• Playback max. 16 cameras in the same time</li> </ul>	...
Network interface	2 x RJ-45 - 10 / 100 / 1000 Mbps	...
Network functions	Full support via network, Remote records copying, Web-Server built-in	...

ONVIF	✓	...
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) • Android: Free application <a href="#">EasyLive Plus</a> • iOS (iPhone): Free application <a href="#">EasyLive Plus</a>	...
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>	...
Bitrate	max. 640 Mbps	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	192.168.1.3	...
RTSP URL	rtsp://user:password@192.168.1.3:554/1/1 - Main stream rtsp://user:password@192.168.1.3:554/1/2 - Sub stream	...
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	...
PC client access ports	3000, 3001	...
Mobile client access ports	3000, 3001	...
Alarm inputs / outputs	16 / 4	...
Motion Detection	✓	...
Intelligent image analysis	—	...
USB	2 x USB 2.0 + 1 x USB 3.0	...
RS232	1 pcs	...
RS485	2 pcs	...
Mouse support	✓	...
IR remote controller in the set	—	...

Main features	<ul style="list-style-type: none"> <li>• Possibility of operation the disks in RAID JBOD/0/1/5/6/10 array</li> <li>Support for Intelligent Image Analysis function, available in TIANDY cameras : <ul style="list-style-type: none"> <li>• crossing the line (tripwire)</li> <li>• double crossing the line</li> <li>• abandoned/missing object</li> <li>• detection of loitering in a given area</li> <li>• running</li> <li>• parking detection</li> <li>• heat map</li> <li>• scene changing</li> <li>• signal loss indication</li> <li>• License plate recognition</li> <li>• detection of persons on duty</li> <li>• detection of people gathering</li> <li>• Parking monitoring mode</li> <li>• protective helmet detection</li> <li>• people counting</li> <li>• advanced face capture features (max 100 000 faces in the database)</li> </ul> </li> </ul>	...
Power supply	100 V ... 240 V AC	...
Weight	11.8 kg	0.070 kg
Dimensions	540 x 445 x 133 mm	95 x 95 x 50 mm - Internal dimensions 108 x 108 x 52 mm - External dimensions
Supported languages	Polish, English, Albanian, Arabic, Spanish, Dutch, Korean, French, Hebrew, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian	...
Manufacturer / Brand	TIANDY	Elektro-Plast
Guarantee	3 years	2 years