



	<a href="#">IP CAMERA IPC2124LE-ADF28KMC-WL ColorHunter - 4 Mpx 2.8 mm UNIVIEW</a>	<a href="#">IP CAMERA IPC2124LB-ADF28KM-H - 3.7 Mpx 2.8 mm UNIVIEW</a>
		
	710.00 PLN 710.00 PLN	642.51 PLN 642.51 PLN
Standard	TCP/IP	TCP/IP
Sensor	1/3 " Progressive Scan CMOS	1/2.9 " Progressive Scan CMOS
Matrix size	4 Mpx	4 Mpx
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	2.8 mm	2.8 mm
View angle	• 113 ° (manufacturer data) • 97 ° (our tests result)	102 °
Range of IR illumination	30 m	30 m
White light LED illuminator range	30 m	...
S/N ratio	> 52 dB	> 52 dB
RS-485 interface	—	—
Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)	Micro SD memory cards up to 128GB support (possible local recording)
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	—	—
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Speaker built-in</li> <li>• Audio detection</li> <li>• Bi-directional audio streaming support</li> </ul>	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Audio transmission via network,</li> <li>• Audio detection</li> </ul>
Main stream frame rate	25 fps @ 4 Mpx	20 fps @ 4 Mpx 25 fps @ 3 Mpx
Network interface	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)
Network protocols	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, SSL / TLS	...
WEB Server	Built-in	Built-in
Max. number of on-line users	32	32
ONVIF	✓	✓
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>
Default IP address	DHCP or 192.168.1.13	DHCP or 192.168.1.13

Default admin user / password	admin / 123456	admin / 123456
Web browser access ports	80, 554	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>
Mobile client access ports	80	80
Port ONVIF	80	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Mirror - Mirror image</li> <li>• Privacy zones - max. 4</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Sharpness - sharper image outlines</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire) (human silhouette)</li> </ul>	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Mirror - Mirror image</li> <li>• Privacy zones - max. 4</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Sharpness - sharper image outlines</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 750 mA</li> </ul>	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 460 mA</li> </ul>
Power consumption	≤ 9 W	≤ 5.5 W
Housing	Compact, Metal + Plastic	Compact, Metal + Plastic
Color	White	White
"Index of Protection"	IP67	IP67
Vandal-proof	—	—
Operation temp	-30 °C ... 60 °C	-30 °C ... 60 °C
Weight	0.41 kg	0.38 kg
Dimensions	191 75 x 74 mm	166 x 63 x 62 mm

Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	UNIVIEW	UNIVIEW
Guarantee	3 years	3 years