




	MOUNTING SCREWS SM-6/RACK	AC POWER SUPPLY ADAPTER AWT-682 PULSAR	AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA HAC-HDBW1500E-0280B-S2 - 5 Mpx 2.8 mm DAHUA
			
	2.56 PLN 2.56 PLN	115.00 PLN 115.00 PLN	396.00 PLN 396.00 PLN
Adapter type	...	Transforming	...
Power voltage	...	230 V AC	...
Frequency range	...	50 Hz	...
Standard	AHD / HD-CVI / HD-TVI / CVBS
Sensor	1/2.7 " Progressive Scan CMOS
Output voltage	...	• 18 V AC, • 20 V AC	...
Package includes	• 4 x M6 screw, • 4 x cage nut, • 4 x plastic shoulder washer, which protects the varnish coating of panels from damage during tightening the screws
Matrix size	5 Mpx
Material	Steel galvanized
Maximal load	...	• 3.3 A @ 18 V AC, • 3 A @ 20 V AC	...
Environment class	...	II	...
Output power	...	60 VA	...
Application	Rack 19" / Rack 10"	• to alarm systems powering • to automatic systems • to low-voltage light installation powering	...
Output	...	2 pcs	...
Resolution	2880 x 1620 - 5 Mpx @ HD- CVI : Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 960 x 576 - 960H, PAL
Range of IR illumination	30 m
IR illuminator power adjustment	Automatic
Lens	2.8 mm, F1.85

View angle	<ul style="list-style-type: none"> • 98 ° (manufacturer data) • 103 ° @ HD-CVI / 90 ° @ AHD / HD-TVI (our tests result)
IR illuminator support	ICR - Movable InfraRed filter
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2-DNR - Digital Noise Reduction • BLC - configurable Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Day/night mode • Auto White Balance • Privacy zones
OSD menu	OSD menu available via recorder
Power supply	12 V DC / 330 mA
Power consumption	≤ 4.2 W
Housing	Dome, Metal
Color	White
"Index of Protection"	...	IP43	IP67
Vandal-proof	IK10
Operation temp	-40 °C ... 60 °C
Weight	0.037 kg	1.29 kg	0.33 kg
Dimensions	<ul style="list-style-type: none"> • 19.9 mm - Total length • 15.5 mm - Thread length 	124 x 75 x 65 mm	Ø 110 x 81 mm
Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Italian
Manufacturer / Brand	...	PULSAR	DAHUA
Guarantee	2 years	2 years	3 years