



	<a href="#">ACCESS CONTROLLER MC16-PAC-EX-1-KIT ROGER</a>	<a href="#">CABLE TIE OPC-350X3.6/W*P100</a>
		
	1825.00 PLN 1825.00 PLN	9.00 PLN 9.00 PLN
Number of served transitions	1 (two-way)	...
Support	RACS 5 v2 (Roger)	...
Number of supported readers	4 pcs	...
In package	...	<b>100 pcs The price for package</b>
Battery backup support	max. 7 Ah	...
Length	...	350 mm
Input lines	8 pcs	...
Width	...	3.6 mm
Output lines	8 pcs	...
Material	...	Nylon 66
Tensile strength	...	180 N
Color	...	White
Communication	<ul style="list-style-type: none"> <li>• RS-485,</li> <li>• RACS 5 v2 (Roger),</li> <li>• Wiegand</li> </ul>	...
Power supply	230 V AC	...
Resistant to	...	<ul style="list-style-type: none"> <li>• UV radiation</li> <li>• oil</li> <li>• gasoline</li> <li>• sea water</li> <li>• solvents</li> <li>• mold</li> <li>• diluted weak organic acids and alkaline compounds</li> </ul>
Melting temperature	...	250 °C
Bundle diameter	...	3 ... 90 mm

Main features	<ul style="list-style-type: none"> <li>• Metal housing</li> <li>• Power output : 1 x 0.2 A, 1 x 1.0 A</li> <li>• Power adapter : 24 V DC / 2.2 A,</li> <li>• Battery charging current : 0.3 A</li> <li>• Protection against deep discharge of the battery</li> <li>• Tamper detection - opening the enclosure</li> <li>• Place for battery - 12 V / 7 Ah</li> <li>• Integrated support in VISO EX software</li> <li>• Functions in the VISO EX system: - MSSQL database</li> <li>- work in distributed systems ...</li> <li>- multi-station work</li> <li>- monitoring of transitions with video preview</li> <li>- T&amp;A event reporting</li> <li>- maximum number of transitions in the system - unlimited</li> <li>- division of the system into partitions operated by independent operators</li> <li>- tool for integration with RACS5 (API) systems</li> <li>- integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)</li> </ul>	
Operation temp	5 °C ... 40 °C	-10 °C ... 80 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)	...
Weight	3.88 kg	...
Dimensions	405 x 365 x 120 mm	...
Manufacturer / Brand	ROGER	...
Guarantee	3 years	2 years