



	<a href="#">IP SPEED DOME CAMERA OUTDOOR IPC6612SR-X33-VG LightHunter - 1080p 4.5 ... 148.5 mm UNIVIEW</a>	<a href="#">FINAL SOCKET DAK1.01/11-SIMON54 TV</a>
		
	6708.72 PLN 6708.72 PLN	25.47 PLN 25.47 PLN
Standard	TCP/IP	...
Mount	...	Flush-mounted, Claw or screw mounting
Sensor	1/2.8 " Progressive Scan CMOS	...
Sockets type	...	1 pcs TV - IEC male
Matrix size	2.1 Mpx	...
Connector	...	screw terminals
TV frequency range	...	<ul style="list-style-type: none"> <li>• 5 ... 70 MHz</li> <li>• 120 ... 862 MHz</li> </ul>
TV tap attenuation	...	1 dB
Application	...	Simon 54 product series, for Nature, Premium frames
Resolution	1920 x 1080 - 1080p , 1280 x 960 1.3 Mpx , 1280 x 720 720p	...
Main features	...	It has DC pass for TV line
Lens	4.5 ... 148.5 mm	...
View angle	56 ° ... 2.6 °	...
Optical zoom	x 33	...
Digital zoom	—	...
Range of IR illumination	150 m	...
Video output	—	...
Preset rotation speed	<ul style="list-style-type: none"> <li>• 180 °/s (horizontal)</li> <li>• 80 °/s (vertical)</li> </ul>	...
Rotation speed (manual control)	<ul style="list-style-type: none"> <li>• 2 °/s ... 75 °/s (horizontal)</li> <li>• 2 °/s ... 75 °/s (vertical)</li> </ul>	...
Horizontal rotation range	360 ° - continuous	...
Vertical rotation range	-15 ° ... 90 °	...
RS-485 interface	✓	...
Number of presets	1024	...
Horizontal scan	✓	...
Route settings	16	...
Image compression method	Ultra H.265 / H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	2 / 1	...
Audio	<ul style="list-style-type: none"> <li>• External microphone input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Audio detection</li> </ul>	...

Main stream frame rate	25 fps @ 1080p	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	32	...
ONVIF	✓	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Mobile phones support	Port 37777 • Android: Free application <a href="#">EZView</a> • iOS (iPhone): Free application <a href="#">EZView</a>	...
Default IP address	DHCP or 192.168.1.13	...
Default admin user / password	admin / 123456	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...

Main features	<ul style="list-style-type: none"> <li>• Intelligent Object Tracking</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• Configurable Privacy Zones - 24</li> <li>• Motion Detection</li> <li>• Tamper signaling</li> <li>• Image rotation and mirror</li> <li>• Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions</li> <li>• Overvoltage protection : 6 kV</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 12 V DC / 3 A (power adapter included)</li> </ul>	...
Power consumption	≤ 25 W	...
Housing	Speed Dome, Metal + Plastic	...
Color	White + Black	White (RAL 9003)
Operation temp	-40 °C ... 65 °C	...
"Index of Protection"	IP66	...
Vandal-proof	—	...
Weight	3.5 kg	0.05 kg
Dimensions	Ø 220 x 370 mm	<ul style="list-style-type: none"> <li>• 75 x 75 x 38 mm</li> <li>• 28 mm - mounting depth</li> </ul>
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian	...
Manufacturer / Brand	UNIVIEW	KONTAKT Simon
Guarantee	2 years	6 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00