



	NVR APTI-N3212AI-I3 32 CHANNELS	OPTICAL ANTI FOAM DETECTOR SPL-TO SATEL
		
	878.40 PLN 878.40 PLN	52.00 PLN 52.00 PLN
Detection	...	Foaming
Standard	TCP/IP	...
Range	...	110 mm
Supported resolutions	max. 12 Mpx - 4000 x 3000 px	...
Alarm signaling	...	LED indicator, Signal to control panel
Video outputs	1 pcs HDMI 4K 1 pcs VGA	...
Application	...	<ul style="list-style-type: none"> • SPL-2030 • SPL-5010 • SPL-5020
Audio support	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras, • Bi-directional audio streaming support • Compliance with the AAC standard 	...
Audio inputs	1 pcs CINCH	...
Audio outputs	1 pcs CINCH	...
Image compression method	H.265+ / H.265 / H.264+ / H.264	...
Bitrate	320 Mbps	...
Supported hard drives	2 x 10 TB SATA	...
Recording modes	Manual, Sensor, Motion detection, Schedule	...
External storage devices backup	Records backup at (.avi) format to USB (pendrive)	...
Searching and playback the records	Records searching: timeline or file list. Playback: forward, fast Playback max. 16 cameras in the same time @ 1080p	...
Network interface	1 x RJ-45 10/100/1000 Base-TX	...
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Network protocols	IPv6, TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE	...
ONVIF	✓	...
Default IP address	192.168.1.88	...
Default admin user / password	admin / 12345	...
Web browser access ports	80, 5000, 554	...
PC client access ports	80, 5000, 554	...
Mobile phones support	Access by a cloud (P2P) • Android: Free application BitVision , Android: Free application iVMS320 • Android: Free application BitVision , iOS: Free application iVMS320	...
USB	• 1 pcs USB 2.0 • 1 pcs USB 3.0	...
Serial ports	—	...
Alarm inputs / outputs	4 / 1	...
PTZ control	IP Speed Dome Cameras	...
Motion Detection	Split the screen into zones : 22 x 18 motion zones	...
Intelligent image analysis	✓	...
Main features	• Support for intelligent image analysis, available in cameras from the APTI-AI series • D-ZOOM - Digital Zoom	...
Mouse support	✓	...
IR remote controller in the set	—	...
Power supply	12 V / 4 A (power adapter included)	12 V DC / 50 mA
Power consumption	≤ 15 W (without HDD)	...
Operation temp	-10 °C ... 50 °C	-35 °C ... 55 °C
Weight	2.71 kg	0.02 kg
Dimensions	380 x 323 x 51 mm	140 x 17 mm
Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Ukrainian, Italian	...
Manufacturer / Brand	APTI	SATEL
Guarantee	2 years	2 years