



| | IP CAMERA APTI-AI401CA3-36W - 4 Mpx 3.6 mm | TV OR MONITOR MOUNT BRATECK-LCD-503AN |
|-------------------------------------|--|--|
| |  |  |
| | 232.00 PLN 232.00 PLN | 45.63 PLN 45.63 PLN |
| Standard | TCP/IP | ... |
| Matrix size | 4 Mpx | ... |
| Sensor | 1/3 " Progressive Scan CMOS | ... |
| Mounting standard | ... | VESA 75, 100, 200x100, 200 |
| Screen size range | ... | 23 " ... 43 " |
| Bearing capacity | ... | 30 kg |
| Distance from mounting surface | ... | 101 ... 463 mm |
| Tilt adjustment | ... | -15 ° ... 15 ° |
| Horizontal rotation | ... | -90 ° ... 90 ° |
| Rotation in the plane of the screen | ... | — |
| Resolution | 2688 x 1512 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p | ... |
| Lens | 3.6 mm | ... |
| View angle | 81 ° | ... |
| Range of IR illumination | 25 m | ... |
| Image compression method | H.265+ / H.265 / H.264+ / H.264 / MJPEG | ... |
| Main stream frame rate | 25 fps @ 4 Mpx | ... |
| Network interface | 10/100 Base-T (RJ-45) | ... |
| Memory card slot | — | ... |
| Alarm inputs / outputs | — | ... |
| Audio | • External microphone input, • Compliance with the AAC standard | ... |
| WEB Server | Built-in | ... |
| Max. number of on-line users | 10 | ... |
| ONVIF | ✓ | ... |
| RS-485 interface | — | ... |
| Mobile phones support | Port no.: 80 or access by a cloud (P2P) • Android: Free application BitVision • iOS (iPhone): Free application BitVision | ... |
| Default IP address | 192.168.1.168 | ... |

| | | |
|-------------------------------|--|---------|
| Default admin user / password | admin / admin The administrator password should be set at the first start | ... |
| Web browser access ports | 80 | ... |
| PC client access ports | 80 | ... |
| Mobile client access ports | 80 | ... |
| Port ONVIF | 80 | ... |
| RTSP URL | <ul style="list-style-type: none"> • rtsp://user:password@ip_address:80/0 - Main stream • rtsp://user:password@ip_address:80/1 - Sub stream | ... |
| Main features | <ul style="list-style-type: none"> • Intelligent image analysis : intrusion, motion detection based on human detection, video tampering • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • Flicker Control - The technology eliminates the tiring eyes flickering image effect • Mirror - Mirror image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Possibility to change the resolution, quality and bit rate • Day/Night mode - configurable • RESET button - on the cable • Privacy zones - max. 3 • Sharpness - sharper image outlines | ... |
| Power supply | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 290 mA | ... |
| Power consumption | ≤ 3.5 W | ... |
| Housing | Compact - Metal | ... |
| Color | White | Black |
| "Index of Protection" | IP67 | ... |
| Operation temp | -20 °C ... 60 °C | ... |
| Weight | 0.44 kg | 1.80 kg |

| | | |
|----------------------|---|---------------------------------|
| Dimensions | 173 x 73 x 73 mm | 220 x 220 x (101 ... 463) mm |
| Supported languages | Polish, English, Bulgarian Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian | ... |
| Manufacturer / Brand | APTI | BRATECK |
| Guarantee | 2 years | 2 years |