



	TURNBUCKLE VANT-6/PL	IP CAMERA DS-2CD2347G2-LU(2.8MM)(C)(BLACK) ColorVu - 4 Mpx Hikvision
		
	8.59 PLN 8.59 PLN	1542.00 PLN 1542.00 PLN
Application	Steel lines	...
Standard	...	TCP/IP
Sensor	...	1/1.8 " Progressive Scan CMOS
Material	Metal	...
Scanning system	...	Progressive
Matrix size	...	4 Mpx
Main features	<ul style="list-style-type: none"> • Screw diameter 6 mm • Work load 70 kg • Corrosion resistance 	...
Resolution	...	2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Lens	...	2.8 mm
View angle	...	<ul style="list-style-type: none"> • 112 ° (manufacturer data) • 104 ° (our tests result)
White light LED illuminator range	...	30 m
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	Microphone built-in
Main stream frame rate	...	25 fps @ 4 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv4/IPv6, UDP, Bonjour, SSL / TLS, PPPoE, SNMP, ARP
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	18.12

Main features	...	<ul style="list-style-type: none"> • Possibility to turn off the LED illuminator • WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Configurable Privacy Zones • Sharpness - sharper image outlines • Filtering of false alarms based on the recognition of persons and vehicles • Motion Detection - classification of people and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing, video tampering, detection of entry into the area / exit from the area, face detection
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 550 mA
Power consumption	...	$\leq 7.6 \text{ W @ PoE}$ $\leq 6.6 \text{ W @ 12 V DC}$
Housing	...	Dome, Aluminum + Plastic
Color	...	Black
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.05 kg	0.76 kg
Dimensions	140 x 20 x 7 mm	Ø 138 x 125 mm

Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand	...	Hikvision
SAP Code	...	311316463
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00