



	<a href="#">IP VANDALPROOF CAMERA IPC3614LE-ADF28KC-WL-BLACK ColorHunter - 4 Mpx 2.8 mm UNIVIEW</a>	<a href="#">IP CAMERA IPC3624LE-ADF28K-WL ColorHunter - 4 Mpx 2.8 mm UNIVIEW</a>
		
	641.83 PLN 641.83 PLN	891.65 PLN 891.65 PLN
Standard	TCP/IP	TCP/IP
Sensor	1/3 " Progressive Scan CMOS	1/1.8 " Progressive Scan CMOS
Matrix size	4 Mpx	4 Mpx
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
Lens	2.8 mm @ F1.6	2.8 mm @ F1.0
View angle	<ul style="list-style-type: none"> <li>• 113 ° (manufacturer data)</li> <li>• 97 ° (our tests result)</li> </ul>	<ul style="list-style-type: none"> <li>• 110 ° (manufacturer data)</li> <li>• 110 ° (our tests result)</li> </ul>
White light LED illuminator range	30 m	30 m
Range of IR illumination	30 m	...
S/N ratio	> 52 dB	> 52 dB
RS-485 interface	—	—
Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)	Micro SD memory cards up to 128GB support (possible local recording)
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	—	—
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Speaker built-in</li> <li>• Bi-directional audio streaming support</li> <li>• Audio transmission via network</li> <li>• Audio detection</li> </ul>	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> <li>• Audio detection</li> </ul>
Main stream frame rate	25 fps @ 4 Mpx	25 fps @ 4 Mpx
Network interface	10/100 Base-TX (RJ-45)	10/100 Base-TX (RJ-45)
Network protocols	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL / TLS, IEEE 802.1x, SNMP	...
WEB Server	Built-in	Built-in
Max. number of on-line users	32	32
ONVIF	✓	✓
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>
Default IP address	DHCP or 192.168.1.13	DHCP or 192.168.1.13

Default admin user / password	admin / 123456	admin / 123456
Web browser access ports	80, 554	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>
Mobile client access ports	80	80
Port ONVIF	80	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	<ul style="list-style-type: none"> <li>• ColorHunter - colorful night mode</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• WB - White Balance (ATW/AWB/manual/indoor/outdoor)</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Sharpness - sharper image outlines</li> <li>• Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms</li> <li>• Privacy zones - max. 4</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion (human silhouette)</li> <li>• Overvoltage protection : 4 kV</li> </ul>	<ul style="list-style-type: none"> <li>• ColorHunter - colorful night mode</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Auto White Balance</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Sharpness - sharper image outlines</li> <li>• Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms</li> <li>• Privacy zones - max. 4</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion (human silhouette)</li> <li>• Overvoltage protection : 4 kV</li> </ul>
Power supply	• PoE (802.3af), • 12 V DC / 670 mA	• PoE (802.3af), • 12 V DC / 500 mA
Power consumption	≤ 8 W	≤ 5.9 W
Housing	Dome, Metal + Plastic	Dome, Metal + Plastic
Color	Black	White
"Index of Protection"	IP67	IP67

Vandal-proof	IK10	—
Operation temp	-30 °C ... 60 °C	-30 °C ... 60 °C
Weight	0.31 kg	0.46 kg
Dimensions	Ø 118 x 96 mm	Ø 118 x 106 mm
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	UNIVIEW	UNIVIEW
Guarantee	3 years	3 years