



	<a href="#">POWER DISTRIBUTION UNIT ACAR-P7 (5 + 2 OUTLETS)</a>	<a href="#">POWER DISTRIBUTION UNIT ACAR-F5/FA/RACK</a>
		
	13.74 GBP 13.74 GBP	23.04 GBP 23.04 GBP
Rated voltage	230 V AC / 50 Hz	230 V AC / 50 Hz
Nominal load current	...	max. 10 A (total)
Total maximal current	10 A	...
Maximal total load	2300 W	2300 W
Number of outlets	5 grounded outlets 10A/250V 2 non-grounded outlets 2.5A/250V	5 grounded outlets 10A/250V
Automatic delayed fuse	10 A / 250 V	10 A / 250 V
Leak current	< 0.5 mA	...
Nominal voltage of surge suppressor	250 V / 50 Hz	250 V / 50 Hz
Protection level of surge suppressor	≤ 1.3 kV (L/N)	≤ 1.3 kV (L/N)
Nominal stroke current	2 kA (L/N) - (8/20μs)	2 kA (L/N) - 8/20 μs
Response time	< 25 ns	< 25 ns
Switch	two-way, with light indication	two-way, with light indication
Maximum stroke current	6.5 kA (L/N) - (8/20μs)	10 kA (L/N) - 8/20 μs 2 type
Main features	...	<ul style="list-style-type: none"> <li>• Current paths shutters</li> <li>• DC filter to eliminate interferences : ≤ 35 dB</li> </ul>
Housing	Plastic - non-flammable	RACK 19", 1U, Plastic - non-flammable
Weight	0.44 kg	0.93 kg
Dimensions	370 x 65 x 44 mm	484 x 54 x 55 mm
Length of the cable	1.45 m	2.9 m
Guarantee	2 years	2 years