



	ANGULAR COMPRESSION PLUG BNC-WK/ZAC-RG59	COMPRESSION PLUG BNC-W/ZAC-TRI113/MSR
		
	4.59 PLN 4.59 PLN	3.71 PLN 3.71 PLN
Connector type	BNC Angular plug	BNC Straight plug
Attachment of connector elements	Compression mounting	Compression mounting
Impedance	75 Ω	75 Ω
Material	Brass (Nickel-plated)	Brass (Nickel-plated)
Application	Coaxial cable	Coaxial cable
Dielectric diameter	max. 5.7 mm	...
Wire mounting	Pressing	Pressing
Cable diameter	max. 8.5 mm	max. 8.0 mm
Shield fastening	Compression mounting	Compression mounting
Watertightness	✓	✓
Example of application	RG59	Triset113
Main features	<ul style="list-style-type: none"> • Wide frequency range • Very low loss in the whole operating band • Perfect matching to the transmission line within the whole operating band • Watertightness of connector with cable connection • Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric • Properly compressed connection is highly resistant to break • Many patent-pending solutions • Wire : 0.55 ... 0.80 mm • To crimp use the crimping tool ZAC/MSR-2K, HT-5082R 	<ul style="list-style-type: none"> • Wide frequency range • Watertightness of connector with cable connection • Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric • Very low loss in the whole operating band • Perfect matching to the transmission line within the whole operating band • Properly compressed connection is highly resistant to break • Many patent-pending solutions • To crimp use the crimping tool HT-5082R
Weight	0.024 kg	0.015 kg
Dimensions	14.5 x 40 x 28 mm	Ø 14.4 x 37 mm
Guarantee	2 years	2 years