



	RS-232 PORT SNIFFER OVER RS-485 SNIF-42	MICROWAVE RADAR DS-PR1-60 Hikvision
		
	208.41 SEK 208.41 SEK	26989.22 SEK 26989.22 SEK
RS-232 capturing data line	TXD (pin 3)	...
Application	...	Outdoor
Range RS-485	1200 m	...
Sensor type	...	Microwave (MW)
Recommended installation height	...	1.2 m ... 4 m
Range	...	60 m
Main features	<ul style="list-style-type: none"> • Data capturing from TXD line of the RS-232 cable • Applies to data transmission from PC to the fiscal printer 	...
Detection angle	...	100 °
Sensitivity adjustment	...	Automatic
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	HTTP, DNS, NTP, TCP, UDP, DHCP, ARP, SSH
Alarm outputs	...	3 pcs : 0.5 A / 125 V AC 1 pcs : 10 A / 240 V AC
LED indication	...	✓
Microwave frequency band	...	24 GHz
Pet immunity	...	max. 20 kg
Antimask feature	...	✓
Target speed range	...	-8.7 ... +8.7 m/s

Main features	...	<ul style="list-style-type: none"> • Maximum number of objects to be observed : 32 • Immunity to environmental changes • Creep zone control • Display the position and direction of an object and the path it has traveled through it • Detection of non-standard moving objects (crawling, squatting or kneeling) • Ability to work with up to 4 Speed Dome cameras for automatic tracking of objects detected by the radar • Tamper detection - opening the enclosure, removing from mounting surface • RESET button
Power supply	12 V DC / 0.1 A (power adapter not included)	<ul style="list-style-type: none"> • 12 V DC / 500 mA • PoE (802.3at)
Power consumption	...	max. 10 W
Operation temp	...	-40 °C ... 65 °C
Color	...	White
"Index of Protection"	...	IP67
IK rating	...	IK09
Weight	0.076 kg	1.84 kg
Dimensions	119 x 63 x 30 mm	228 x 206 x 61 mm
Manufacturer / Brand	DELTA	Hikvision
SAP Code	...	302401144
Guarantee	3 years	3 years