



	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE16D0T-IRF(2.8mm)(C) - 1080p Hikvision	IP CAMERA DS-2CD2T63G2-2I(2.8MM) ACUSENSE - 6 Mpx Hikvision
		
	220.00 PLN 220.00 PLN	1082.00 PLN 1082.00 PLN
Standard	AHD / HD-CVI / HD-TVI / PAL	TCP/IP
Sensor	Progressive Scan CMOS	1/2.8 " Progressive Scan CMOS
Matrix size	2.1 Mpx	6 Mpx
Resolution	1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI 960 x 576 @ PAL	3200 x 1800 - 6 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	2.8 mm	2.8 mm
View angle	• 106 ° (manufacturer data) • 100 ° (our tests result)	107 °
IR illuminator power adjustment	Automatic	...
Compression	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Range of IR illumination	25 m	60 m
Alarm inputs / outputs	...	—
Audio	...	—
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Video output	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL, BNC socket	...
OSD menu	✓	...
Main stream frame rate	...	• 20 fps @ 6 Mpx • 25 fps @ 4 Mpx
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	✓
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.64
Web browser access ports	...	80

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
RS-485 interface	...	—
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • IR illuminator optimization • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Day/night mode • Sharpness - sharper image outlines 	<ul style="list-style-type: none"> • Camera from AcuSense series • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ROI - improve the quality of selected parts of image • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream • NAS - Network Attached Storage support • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • Configurable Privacy Zones • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Image rotation and mirror • Filtering of false alarms based on the recognition of persons and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, video tampering, face detection
Power supply	12 V DC / 250 mA	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 670 mA
Power consumption	≤ 3 W	<ul style="list-style-type: none"> • ≤ 9 W @ PoE (802.3af) • ≤ 8 W @ 12 V DC
Housing	Compact, Metal	Compact, Aluminum alloy
Color	White	White + Black
"Index of Protection"	IP67	IP67
Operation temp	-40 °C ... 60 °C	-30 °C ... 60 °C

Supported languages	Polish, English	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian
Weight	0.26 kg	1.08 kg
Dimensions	Ø 70 x 138 mm	Ø 105 x 293 mm
Manufacturer / Brand	Hikvision	Hikvision
SAP Code	300511939	311315970
Guarantee	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00