



	SPEAKER CABLE HI-FI/2X0.35	ROUTER ARCHER-C50 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP-LINK
		
	0.89 PLN 0.89 PLN	145.78 PLN 145.78 PLN
Frequency range	...	2.4 GHz, 5 GHz
Antenna type	...	4 x Omnidirectional antenna
In section	100 m . Price for 1m when buying a whole roll	...
Standards	...	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz
Inner conductor	2 x Ø 0.35 mm Cu-OFC Stranded wire	...
Outer coating	PVC	...
Baud rates	...	300 Mbps + 867 Mbps
Coating color	Colorless	...
LAN ports	...	4 x 10/100 Mbps LAN 1 x 10/100 Mbps Uplink
LED indicators	...	Power, 2.4 GHz WLAN, 5 GHz WLAN, Ethernet, WAN, WPS
Receiver sensitivity	...	2.4 GHz : • 11g 54M : -76 dBm • 11n HT20 MCS7 : -74 dBm • 11n HT40 MCS7 : -71 dBm 5 GHz : • 11a 54M : -77 dBm • 11ac VHT20 MCS8 : -72 dBm • 11ac VHT40 MCS9 : -68 dBm • 11ac VHT80 MCS9 : -63 dBm
DDNS	...	✓
DHCP server	...	✓
Firmware update	...	✓
Protections	...	WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding

Management interface	...	Web browser, TP-LINK Tether
Power supply	...	9 V DC / 0.85 A (power adapter included)
Main features	...	<ul style="list-style-type: none"> • Firewall • Internet access filtering • Static / dynamic routing • Built-in 4-port switch • Wireless transmission statistics • The WPS function allows to easy establish an encrypted connection • QoS • WMM (Wi-Fi Multimedia) • Rate limit • Access control • Remote management • DMZ • parental control • Guest Network - a separate and secure network for guests • SSID hiding
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Weight	...	0.30 kg
Dimensions	...	230 x 145 x 34 mm
Manufacturer / Brand	...	TP-LINK
Guarantee	2 years	3 years