



	IP CAMERA DS-2CD2083G2-I(2.8MM) ACUSENSE - 8.3 Mpx Hikvision	VOLTAGE DISTRIBUTION PANEL VDP19-3U-B
		
	1296.00 PLN 1296.00 PLN	71.53 PLN 71.53 PLN
Width	...	19 "
Standard	TCP/IP	...
Height	...	3 U
Material	...	Steel - powder painted
Sensor	1/2.8 " Progressive Scan CMOS	...
Matrix size	8.3 Mpx	...
Application	...	RACK 19"
Main features	...	<ul style="list-style-type: none"> • DIN TS-35 rail • Corrosion resistance • Possibility to mount of 24 fuses, 1 S wide • 6-point fixing to the front RACK rails • 6 pcs. of M6 screws with cage nuts included • Main cable entries on the back of the enclosure
Resolution	3840 x 2160 - 8.3 Mpx , 3200 x 1800 - 5 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Lens	2.8 mm	...
View angle	107 °	...
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Range of IR illumination	40 m	...
Alarm inputs / outputs	—	...
Audio	—	...
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)	...
Main stream frame rate	25 fps @ 8.3 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	✓	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect	...
Default IP address	192.168.1.64	...

Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ 	...
RS-485 interface	—	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • ICR - Movable InfraRed filter • Configurable Privacy Zones • Smart motion detection (with recognizing people and vehicles) • Filtering of false alarms based on the recognition of persons and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, face detection 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA 	...
Power consumption	<ul style="list-style-type: none"> • ≤ 7.2 W @ PoE (802.3af) • ≤ 6 W @ 12 V DC 	...
Housing	Compact, Metal	...
Color	White	Black (RAL 9005)
"Index of Protection"	IP67	...
Operation temp	-30 °C ... 60 °C	...
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian	...
Weight	0.5 kg	1.48 kg
Dimensions	Ø 70 x 162 mm	<ul style="list-style-type: none"> • 445 x 127 x 59 mm Internal dimensions • 485 x 130 x 61 mm External dimensions

Manufacturer / Brand	Hikvision	...
SAP Code	311316039	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00