

	EXPANSION PLUG KS-10/6X100 KLIMAS	MULTI-SOCKET PLUG WITH SURGE PROTECTION ACAR-MINI-AGD	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE16H0T- ITF(2.8MM)(C) - 5 Mpx Hikvision
			
	1.06 PLN 1.06 PLN	41.48 PLN 41.48 PLN	280.00 PLN 280.00 PLN
Rated voltage	...	230 V AC / 50 Hz	...
Total maximal current	...	10 A	...
Maximal total load	...	2300 W	...
Material	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized
Standard	AHD / HD-CVI / HD-TVI / PAL
Sensor	Progressive Scan CMOS
Response time	...	< 25 ns	...
Drilling diameter	10 mm
Matrix size	5 Mpx
Number of outlets	...	2 grounded outlets 10A/250V	...
Expansion plug length	60 mm
Maximal voltage	...	250 V / 50 Hz	...
Screw dimensions	Ø 6 x 100 mm, SW-10
Protection level of surge suppressor	...	≤ 1.3 kV (L/N)	...
Nominal stroke current	...	2 kA (L/N) - (8/20µs)	...
Application	<ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick
Maximum stroke current	...	10 kA (L/N) - (8/20µs)	...
Electric shock protection system	...	Ground connectors (pins) connected with ground wire of AC mains	...
Resolution	<ul style="list-style-type: none"> • 2560 x 1944 - 5 Mpx @ AHD / HD-TVI, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI • 1920 x 1080 @ HD-TVI • 960 x 576 @ PAL
Lens	2.8 mm
View angle	<ul style="list-style-type: none"> • 85 ° (manufacturer data) • 80 ° (our tests result)
Range of IR illumination	30 m

IR illuminator power adjustment	Automatic
Video output	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL, BNC socket
Audio	—
OSD menu	✓
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines
Power supply	12 V DC / 360 mA
Power consumption	≤ 4.3 W
Housing	...	Plastic - non-flammable	Compact, Metal
Color	White + Black
"Index of Protection"	IP67
Operation temp	-40 °C ... 60 °C
Weight	...	0.12 kg	0.26 kg
Dimensions	...	131 x 55 x 75 mm	139 x 58 x 61 mm
Supported languages	English
Manufacturer / Brand	KLIMAS	...	Hikvision
SAP Code	300512117
Guarantee	2 years	2 years	3 years