



	UPS AT-UPS1200BK-LCD 1200 VA EAST	THERMOSTAT KTO-011
		
	471.81 PLN 471.81 PLN	24.00 PLN 24.00 PLN
Sensor type	...	Bimetallic
Nominal power	720 W	...
Apparent Power	1200 VA	...
Contact type	...	NC - opened after exceeding the set temperature
Maximal power voltage	...	250 V AC
Input voltage	173 V ... 287 V AC	...
Relay maximal load	...	10 A
Input frequency	50 / 60 Hz (auto detection)	...
Temperature set range	...	0 °C ... 60 °C
Output voltage	230 V AC ± 10 % (Approximated Sine Wave)	...
Hysteresis	...	7 °C ± 4 °C
Operation temp	...	-20 °C ... 80 °C
Output frequency	50 / 60 Hz ± 1 %	...
"Index of Protection"	...	IP20
Assembly	...	DIN TS-35 rail
Transfer time	2 ... 7 ms (typical), max. 10 ms	...
Charging time (recover to 90% capacity)	8 hours	...
Battery	2 pcs - 12V/7Ah	...
Estimated battery operation time	<ul style="list-style-type: none"> • 57 minutes @ 100 W • 14 minutes @ 300 W • 8 minutes @ 500 W 	...
Number of outputs	3 pcs CEE 7/3 (Schuko)	...
Protections	<ul style="list-style-type: none"> • Fuse • Overvoltage • Overload protection • Overcharge protection • Ethernet line filter 	...
Operation state indication	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, • Sound signaling 	...

Main features	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Automatic Voltage Regulator (AVR) • Compatible with power generators • Remote management - UPSmart application included • Built-in EMI, RFI filter • Configurable alarm 	...
Application	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment 	...
Housing type	Tower	...
Operation temp. / Relative humidity	0 °C ... 40 °C / 20 ... 90 %	...
Weight	8.57 kg	0.040 kg
Dimensions	348 x 173 x 140 mm	60 x 43 x 33 mm
Manufacturer / Brand	EAST	...
Guarantee	2 years	2 years