



	CAMERA CEILING BRACKET PFB2211C DAHUA	IP CAMERA DS-2CD1043G2-LIU(4MM) Smart Hybrid Light - 3.7 Mpx Hikvision
		
	132.00 PLN 132.00 PLN	684.00 PLN 684.00 PLN
Standard	...	TCP/IP
Neck diameter	Ø 126 mm	...
Suitable for cameras	DAHUA	...
Sensor	...	1/3 " Progressive Scan CMOS
Material	Aluminum	...
Matrix size	...	4 Mpx
Distance from mounting surface	475 ... 800 mm	...
Resolution	...	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	4 mm
View angle	...	• 78 ° (manufacturer data) • 76 ° (our tests result)
White light LED illuminator range	...	30 m
Range of IR illumination	...	30 m
Memory card slot	...	—
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	• Microphone built-in • Audio transmission via network • Compliance with the AAC standard • Noise and echo reduction
Main stream frame rate	...	• 20 fps @ 3.7 Mpx • 25 fps @ 1080p
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	✓

Main features	...	<ul style="list-style-type: none"> • Smart Hybrid Light technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Auto White Balance • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Configurable Privacy Zones • Sharpness - sharper image outlines • Smart motion detection (with recognizing people and vehicles)
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 420 mA
Power consumption	...	<ul style="list-style-type: none"> • ≤ 6.5 W @ PoE • ≤ 5 W @ 12 V DC
Housing	...	Compact - Metal + Plastic
Color	White	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.6 kg	0.28 kg
Dimensions	Ø 126 x 475 ... 800 mm	171 x 66 x 69 mm
Supported languages	...	Polish, English, Croatian, Czech, Romanian, Serbian, Slovak, Slovenian, Turkish, Ukrainian, Vietnamese
Manufacturer / Brand	DAHUA	Hikvision

SAP Code	...	311322029
Guarantee	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00