



	IP CAMERA DS-2CD1323G2-LIU(2.8MM) Smart Hybrid Light - 1080p Hikvision	ACCESS CONTROLLER ASI1212F DAHUA
		
	565.00 PLN 565.00 PLN	944.00 PLN 944.00 PLN
Standard	TCP/IP	...
Cards support	...	13.56 MHz S50
Reading distance of prox-keys	...	1 ... 3 cm
Sensor	1/2.9 " Progressive Scan CMOS	...
Keyboard built-in	...	—
Matrix size	2.1 Mpx	...
Autonomous operation	...	✓
Battery backup support	...	—
Input lines	...	3
Output lines	...	3
Resolution	1920 x 1080 - 1080p 1280 x 720 - 720p	...
Identification time	...	< 1.5 s
Lens	2.8 mm	...
View angle	103 °	...
White light LED illuminator range	30 m	...
Communication	...	<ul style="list-style-type: none"> • RS-485 • Wiegand • LAN
Range of IR illumination	30 m	...
RS-485 interface	...	✓
RS-232 interface	...	—
Wiegand interface	...	✓
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
USB	...	—
Memory card slot	—	—
Internal memory	...	Support storage of 150 000 records
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Compliance with the AAC standard • Noise and echo reduction 	...
Main stream frame rate	25 fps @ 1080p	...
Network interface	10/100 Base-T (RJ-45)	10/100 Base-T
WEB Server	Built-in	...

Max. number of on-line users	6	...
ONVIF	✓	...
Main features	<ul style="list-style-type: none"> • Smart Hybrid Light technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • Possibility to turn off the LED illuminator • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Sharpness - sharper image outlines • video tampering • Configurable Privacy Zones • Smart motion detection (with recognizing people and vehicles) 	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	...
Default IP address	192.168.1.64	192.168.1.108



Main features	...	<ul style="list-style-type: none"> • Built-in LCD display 240 x 320 px - 2.8 " capacitive touch screen • Fingerprint reader built-in • Memory of 3000 fingerprint patterns • Possible connection of the external ASR series reader (read in/out door control) • Identification modes : Proximity identifier 13.56 MHz S50, Fingerprint, PIN, Any combination of the above • Remote access verification • Tamper detection - removing from mounting surface • Support for door contact and exit button • Indication of forced entry and the lack of closing doors • 30000 indexed users • Possibility to configure access groups • 128 General Purpose Schedules • 128 time periods within single Schedule • Holiday Schedules • Anti-passback • Integration with an alarm system via in/out line • Remote programming from PC
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
Operation temp	...	-10 °C ... 45 °C
Web browser access ports	80	...
Permissible relative humidity	...	5 ... 90 % (non-condensing)
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...



RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 420 mA 	12 V DC / 1 A
Power consumption	<ul style="list-style-type: none"> • ≤ 6.5 W @ PoE • ≤ 5 W @ 12 V DC 	...
Housing	Dome, Metal + Plastic	...
Color	White	...
"Index of Protection"	IP67	—
Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.36 kg	0.22 kg
Dimensions	Ø 110 x 89 mm	115 x 115 x 32 mm
Supported languages	English, Ukrainian	English
Manufacturer / Brand	Hikvision	DAHUA
SAP Code	311321902	...
Guarantee	3 years	3 years

