



| | | |
|----------------------|---|---|
| | OPTICAL TIME-DOMAIN REFLECTOMETER (OTDR) ZS1000-A-V2 | COMBINATION WRENCH ST-STMT95788-0 10 mm STANLEY |
| |  |  |
| | 2318.40 PLN 2318.40 PLN | 12.46 PLN 12.46 PLN |
| Size | ... | 10 mm |
| Display | 3.5 " - touch screen | ... |
| Length | ... | 143 mm |
| Manufacturer / Brand | ... | STANLEY |
| Optical wavelength | <ul style="list-style-type: none"> • OTDR @ 1310 nm, 1550 nm, • OPM @ 850 nm / 980 / 1270 / 1300 nm / 1310 nm / 1490 nm / 1550 nm / 1577 nm / 1625 / 1650 • OLS : - continuous - 270 Hz / 1 kHz / 2 kHz - pulsed : 1 kHz / 2 kHz | ... |
| Connector type | <ul style="list-style-type: none"> • SC @ OTDR, • 2.5mm universal connector @ OPM / VFL | ... |
| Optical power meter | ✓ | ... |
| VFL | ✓ | ... |
| OLS | ✓ | ... |
| Main features | <ul style="list-style-type: none"> • Measurement range for OTDR meter : 100 m ... 80 km • Built-in VFL laser fiber tester • High measurement accuracy • OPM function - optical power meter • iOLA function - measurement result presented in a simple, graphical form • OLS function - light source 1310 / 1550 nm • Generating reports in *.sor files | <ul style="list-style-type: none"> • Product is made from chrome-vanadium steel, • Full polish chrome plating for strength and durability, and easy cleaning, • Corrosion resistance, • Fork and polygonal head inclined by 15° for better accessibility to the nut or bolt, • Anti-slip profile - wrench profile shape optimizes contact with the bolt, preventing the wrench from slipping, • 12 point versatile ring spanner end for easy installation |

| | | |
|--------------|---|-----------------|
| Power supply | Li-Poly battery 7.4 V / 2000 mAh , Battery charging - from USB-C port (cable included) | ... |
| Weight | 0.22 kg | 0.044 kg |
| Dimensions | 123 x 75 x 31 mm | 143 x 23 x 7 mm |
| Guarantee | 2 years | 2 years |