



	MULTIMEDIA OUTLET GMDF-352	DOUBLE FIBER OPTIC SOCKET DGS2.01/11- SIMON54 SC-APC
		
	64.58 PLN 64.58 PLN	53.01 PLN 53.01 PLN
Mount	Surface-mounted	Flush-mounted, Claw or screw mounting
Sockets type	<ul style="list-style-type: none"> • 1 pcs DATA, • 2 pcs RTV 	2 pcs SC-APC
Connector	...	2 pcs SC-APC socket
TV frequency range	87 ... 1000 MHz	...
Application	...	Simon 54 product series, for Nature, Premium frames
Housing	...	Non-halogen plastic, PC
Radio frequency range	87 ... 1000 MHz	...
Color	...	White (RAL 9003)
Frequency range for DATA line	5 ... 65 MHz	...
TV tap attenuation	87 ... 862 MHz @ 7.5 max. 8.5 dB 862 ... 1000 MHz @ 8.5 max. 9.5 dB	...
Radio tap attenuation	87 ... 862 MHz @ 7.5 max. 8.5 dB 862 ... 1000 MHz @ 8.5 max. 9.5 dB	...
DATA tap attenuation	5 ... 65 MHz @ 9.5 max. 10.5 dB	...
Main features	<ul style="list-style-type: none"> • Full, double galvanic isolation between input and outputs • High voltage input protection 2.12 kV / DC • Protection system against core inverse magnetization due to high level signals • Solid, die-cast metal housing 	...
Weight	0.12 kg	0.048 kg
Dimensions	98 x 80 x 27 mm	<ul style="list-style-type: none"> • 75 x 75 x 50 mm • 33 mm - mounting depth
Manufacturer / Brand	TELMOR	KONTAKT Simon
Guarantee	2 years	6 years