



	UTP / COAXIAL TRANSMITTER EOC-110KIT 2 PCS SET	ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT ASI7213X-T1 - 1080p DAHUA
		
	54.53 CHF 54.53 CHF	3465.09 CHF 3465.09 CHF
LAN ports	1 pcs RJ45 1 pcs BNC socket	...
Sensor	...	1/2.8 " CMOS
Transmission speed	10 / 100 Mbps Half Duplex	...
Transmission range	200 m @ RG6	...
Optical zoom	...	—
Main features	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks 	...
Matrix size	...	2.1 Mpx 120 x 90 px
View angle	...	50 °
Resolution	...	1920 x 1080 - 1080p 120 x 90 px
Standard	...	TCP/IP
Range of IR illumination	...	5 m
White light LED illuminator range	...	5 m
Temperature measurement	...	✓
Temperature measurement range	...	30 °C ... 50 °C
Accuracy of temperature measurement	...	± 0.1 °C
Face recognition distance	...	0.3 m ... 1.8 m (max 100 000 faces in the database)
RFID proximity reader built-in	...	13.56 MHz S50
Internal memory	...	Support storage of 300 000 records

Video output	...	—
RS-485 interface	...	✓
RS-232 interface	...	✓
Wiegand interface	...	✓
USB	...	2 x USB 2.0
Memory card slot	...	—
Alarm inputs / outputs	...	2 / 2 - Relay outputs
Audio	...	Speaker built-in
Network interface	...	<ul style="list-style-type: none"> • 1 x 10/100 Base-T (RJ-45) • 1 x 10/100/1000 Base-T (RJ-45)
Network protocols	...	IPv4, RTSP, RTP, TCP, UDP, P2P
WEB Server	...	Built-in
ONVIF	...	✓
Default IP address	...	192.168.1.108
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777

Main features	...	<ul style="list-style-type: none"> • Temperature measurement • Built-in LCD display showing the image from the video camera and the result of temperature measurement - 7 " capacitive touch screen, 1024 x 600 px • Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above • Wiegand 34/26 • WDR - 120 dB - Wide Dynamic Range • LED indication • Buzzer for acoustic signaling of some system events • AGC - Automatic Gain Control • Sharpness - sharper image outlines • Day/Night mode (color/b&w/auto) • RESET button • AI detection : A solution dedicated to measuring temperature. The camera is able to detect increased object temperature
Power supply	...	12 V DC / 2 A (power adapter included)
Power consumption	...	≤ 24 W
Housing	...	Aluminum + Tempered glass
Color	...	Black + Silver
"Index of Protection"	...	—
Operation temp	...	<ul style="list-style-type: none"> • -10 °C ... 55 °C - without temperature measurement • 15 °C ... 32 °C - with temperature measurement
Weight	0.055 kg (single element)	2 kg
Dimensions	72 x 25 x 25 mm (single element)	313 x 130 x 59 mm
Montage hole diameter	...	37 mm
Supported languages	...	English
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	3 years