



	<a href="#">IP HYBRID THERMAL IMAGING CAMERA TC-C35LQ</a> <a href="#">SPEC:I5W/E/Y/T/6MM/V4.2</a> <a href="#">6.8 mm - 720p. - 5 Mpx</a> <a href="#">6 mm TIANDY</a>	<a href="#">POWER DISTRIBUTION UNIT LE-049494 (6 OUTLETS) 3 m LEGRAND</a>
		
	6631.00 PLN 6631.00 PLN	94.04 PLN 94.04 PLN
Rated voltage	...	230 V AC / 50 Hz
Total maximal current	...	16 A
Pixel pitch	12 µm	...
Maximal total load	...	3680 W
Thermal sensitivity (NETD)	< 55 mK @ F1.1	...
Number of outlets	...	6 grounded outlets 16A/250V CEE 7/5
Fuse	...	—
Spectral range	8 µm ... 14 µm	...
Switch	...	—
Wire gauge	...	3 x 1.5 mm <sup>2</sup>
Length of the cable	...	3 m
Resolution	1280 x 720 px - 720p , 704 x 576 px , 640 x 480 px , 352 x 288 px 2880 x 1620 - 5 Mpx 2688 x 1520 - 4 Mpx 2560 x 1440 - 3.7 Mpx 2304 x 1296 - 3 Mpx	...
Sensor	Uncooled VOx microbolometer 1/2.7 " Progressive Scan CMOS	...
Lens	6.8 mm 6 mm	...
View angle	26 ° 53 °	...
Range of IR illumination	50 m	...
Standard	IP	...
Video output	—	...
RS-485 interface	✓	...

Memory card slot	Micro SD card support up to 512GB	...
Image compression method	S+265 / H.265 / H.264	...
Alarm inputs / outputs	2 / 1	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Speaker built-in</li> <li>• Audio input</li> <li>• Bi-directional audio streaming support</li> <li>• Audio output</li> </ul>	...
Main stream frame rate	<ul style="list-style-type: none"> <li>• 25 fps @ 1280 x 960</li> <li>• 25 fps @ 5 Mpx</li> </ul>	...
Interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	3	...
ONVIF	✓	...
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EasyLive Plus</a></li> <li>• iOS (iPhone): Free application <a href="#">EasyLive Plus</a></li> </ul>	...
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>	...
Default IP address	DHCP or 192.168.1.2	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	...
Mobile client access ports	3000, 3001	...
PC client access ports	3000, 3001	...
Port ONVIF	80	...
Intelligent image analysis	<ul style="list-style-type: none"> <li>• crossing the line (tripwire)</li> <li>• double crossing the line</li> <li>• classification of people and vehicles</li> <li>• intrusion</li> </ul>	...

Main features	<ul style="list-style-type: none"> <li>• WDR - Wide Dynamic Range</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Sharpness - sharper image outlines</li> <li>• Motion Detection</li> <li>• Detection of people smoking cigarettes</li> <li>• High temperature indication</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC</li> </ul>	...
Power consumption	≤ 9 W	...
Housing	Compact - Metal	Plastic
Color	White	White / Gray
"Index of Protection"	IP67	...
Operation temp	-35 °C ... 65 °C	...
Weight	1.47 kg	0.61 kg
Dimensions	327 x 115 x 109 mm	295 x 54 x 37 mm
Supported languages	Polish, Albanian, English, Arabic, Spanish, French, Hebrew, Dutch, Korean, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian	...
Manufacturer / Brand	TIANDY	LEGRAND
Guarantee	3 years	2 years