



	HEX REGULAR NUT N-M8/KL-8	AHD, HD-CVI, HD-TVI, PAL CAMERA APTI-H52C21-36W - 8.3 Mpx, 4K UHD 3.6 mm
		
	0.15 PLN 0.15 PLN	136.00 PLN 136.00 PLN
Size	M8	...
Material	Steel galvanized	...
Strength class	8	...
Main features	DIN 934 compliance	...
Standard	...	AHD, HD-CVI, HD-TVI, PAL
Wrench size	13 mm	...
Sensor	...	1/2.5 " Progressive Scan CMOS
Thickness	6.4 mm	...
Matrix size	...	8.3 Mpx
Resolution	...	3840 x 2160 - 8.3 Mpx, 4K UHD @ AHD / HD-CVI / HD-TVI, 15 fps , 3840 x 2160 - 8.3 Mpx, 4K UHD @ HD-CVI / HD-TVI, 12.5 fps , 2592 x 1944 - 5 Mpx @ AHD / HD-TVI, 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI, 30 fps, 25 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI, 15 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI, 30 fps, 25 fps , 960 x 576 - 960H @ CVBS
Lens	...	3.6 mm
View angle	...	• 77 ° (manufacturer data) • 83 ° (our tests result)
Range of IR illumination	...	25 m
IR illuminator power adjustment	...	Automatic
Video output	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / PAL - selectable by switch, Via OSD
Audio	...	—
OSD menu	...	✓

Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines
Power supply	...	12 V DC / 220 mA
Power consumption	...	≤ 2.7 W
Housing	...	Compact - Metal Plastic
Color	...	White
"Index of Protection"	...	IP67
Operation temp	...	-20 °C ... 50 °C
Weight	0.005 kg	0.24 kg
Dimensions	...	178 x 72 x 72 mm
Supported languages	...	Polish, English, French, Spanish, Portuguese, Russian, Italian
Manufacturer / Brand	...	APTI
Guarantee	2 years	2 years