



	VIDEO DOORPHONE KIT KTD01(F) DAHUA	RFID PROXIMITY CARD ATLO-307NR 13.56 MHz S50
		
	18620.69 CZK 18620.69 CZK	12.84 CZK 12.84 CZK
Standard	...	13.56 MHz S50
Sensor	2 Mpx CMOS	...
Possibility of programming the serial number (ID)	...	—
Lens	1.95 mm	...
Ability to write to internal memory	...	1 kB
View angle	168 °	...
Serial Number overprint	...	✓
proximity reader built-in	—	...
Image compression method	H.265	...
LED illuminator	—	...
IR illuminator	✓	...
RS-485	✓	...
UTP category	UTP cat. 5e	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	...
"Index of Protection"	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	...
IK rating	IK07	...
Shield	7 " capacitive touch screen	...
Resolution	1024 x 600	...
Internal memory	—	...
Memory card slot	Micro SD memory cards up to 64GB support (possible local recording)	...

Main features	<ul style="list-style-type: none"> • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • The ability to automatically take and save photos if you do not answer to the bell button, • The ability to record a short video message in the absence of a response to the bell button, • IP Dahua cameras support 	...
Controlling	capacitive touch screen	...
Alarm inputs	6	...
Alarm outputs	1	...
Material	Aluminum	...
Color	Silver White Silver	...
External dimensions	129 x 163 x 40 mm	...
Number of ports	1 x DAHUA 2-wire , 2 x DAHUA 2-wire - Uplink 2 x RJ-45	...
Compatibility	DAHUA DAHUA 2-wire doorphone installation DAHUA	ISO/IEC 14443A

Main features	<ul style="list-style-type: none"> • SD memory cards up to 32GB support (possible local recording), • LED diodes, • Monitoring the status of individual doors, • WDR - 120 dB - Wide Dynamic Range, • 3D-DNR - Digital Noise Reduction, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - removing from mounting surface, • Possibility to connecting in cascade • Possibility to mount on a wall, or on the DIN TS-35 rail 	<ul style="list-style-type: none"> • Serial Number Format : 8H10D + 6H8D - Reverse number, • Range : ~ 10 cm, • The 6605 chip
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 2-Wire IP interface • PoE (802.3af), • 2-Wire IP interface 48 V / 1 ... 3 A DC	...
Power consumption	≤ 12 W ≤ 6 W (operation) ≤ 2 W (standby) max. 144 W (at full load)	...
Housing	Aluminum Metal	...
Operation temp	-30 °C ... 60 °C -10 °C ... 55 °C -10 °C ... 55 °C	...
Weight	0.33 kg 0.36 kg 0.5 kg 0.242 kg	0.006 kg
Dimensions	130 x 96 x 28.5 mm 189 x 130 x 26 mm 131 x 103 x 40 mm	86 x 54 x 0.8 mm
Supported languages	Polish, English Polish, English English, Bulgarian, Czech, Finnish, Polish, Slovenian, Slovak, Hungarian	...
Manufacturer / Brand	DAHUA	ATLO

Guarantee	3 years	2 years
-----------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00