


	LITHIUM BATTERY BAT-CR2016 ENERGIZER	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1200TRQ-0280B-S6 - 1080p 2.8 mm DAHUA	SWITCH POE GTX-A1-10-82 8-PORT
			
	4.06 PLN 4.06 PLN	170.00 PLN 170.00 PLN	270.40 PLN 270.40 PLN
Rated voltage	3 V
Type	CR2016
Standard	...	HD-CVI, HD-TVI, AHD, CVBS	...
Sensor	...	Progressive Scan CMOS	...
Matrix size	...	2 Mpx	...
LAN ports	<ul style="list-style-type: none"> • 8 x RJ45 (1 x Hi-PoE + 7 x PoE (802.3af/at)), • 2 x RJ45 - Uplink
Resolution	...	1920 x 1080 - 1080p , 960 x 576 - 960H, PAL	...
Range of IR illumination	...	25 m	...
IR illuminator power adjustment	...	Automatic	...
Lens	...	2.8 mm	...
Management	—
View angle	...	<ul style="list-style-type: none"> • 102 ° (manufacturer data) • 103 ° (our tests result) 	...
LED diodes	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Transmission speed	10 / 100 Mbps : 2 x Port LAN - Uplink + 8 x Port LAN & PoE
Audio	...	—	...
Operation modes	<ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • S - Extend - Range : 250 m @ 10 Mbps

Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • Day/night mode • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Auto White Balance • Privacy zones - max. 8 • Mirror - Mirror image • Sharpness - sharper image outlines 	...
OSD menu	...	OSD menu available via DAHUA recorder	...
Maximal output power	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 8 ports
Power consumption	...	≤ 2.7 W	...
Maximal total power	120 W
MAC addresses table	1k
Housing	...	Dome, Plastic	...
"Index of Protection"	...	IP50	...
Color	...	White	...
Vandal-proof	...	—	...
Operation temp	...	-40 °C ... 60 °C	...
Main features	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Auto-learning and Auto-aging functions support for MAC addresses • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • MTBF (Mean Time Between Faults) : 50000 h
Certificates	CE, FCC Class B
Manufacturer / Brand	ENERGIZER	DAHUA	...
Protections	Overvoltage ± 4 kV
Power supply	...	12 V DC / 220 mA	100 ... 265 V AC

Operation temp	-10 °C ... 45 °C
Weight	0.005 kg	0.15 kg	0.76 kg
Dimensions	Ø 20 x 1.6 mm	Ø 97 x 93 mm	210 x 150 x 35 mm
Guarantee	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00