




	<a href="#">ACCESS POINT RG-RAP2260(H) Wi-Fi 6 2.4 GHz 5 GHz 1148 Mbps + 4804 Mbps REYEE</a>	<a href="#">UNIVERSAL MIDDLE CLAMP USP-KW-35 FOR SOLAR PANELS</a>	<a href="#">MOUNTING PROFILE USP-SM-1100 FOR SOLAR PANELS</a>
			
	1231.00 PLN 1231.00 PLN	2.00 PLN 2.00 PLN	57.60 PLN 57.60 PLN
Material	...	Aluminum	Aluminum
Height	...	11 mm	...
Hole diameter	...	9 mm	...
mounting screw	...	M8 x 45 (included)	...
Frequency range	2.4 GHz ( 2.400 ... 2.4835 GHz ) 5 GHz ( 5.150 ... 5.850 GHz )	...	...
Antenna type	4x4 MU-MIMO, 2.4 GHz - 3 dBi / 5.0 GHz - 4 dBi, Integrated - 8 x Omnidirectional antenna	...	...
Standards	IEEE 802.11 a/b/g/n/ac/ax	...	...
Baud rates	1148 Mbps + 4804 Mbps	...	...
Wireless transmission range	40 m - 2.4 GHz 70 m - 5 GHz	...	...
Default IP address	10.44.77.254	...	...
Protections	WPA-PSK, WPA2-PSK, WPA/WPA2-PSK	...	...
LAN ports	2 x 10/100/2500 Mbps	...	...
Mobile phones support	Android: Free application <a href="#">Ruijie Reyee</a> iOS (iPhone): Free application <a href="#">Ruijie Reyee</a>	...	...
Transmitter power	≤ 35 dBm @ 2.4 GHz (max) ≤ 36 dBm @ 5.0 GHz (max)	...	...
Power supply PoE	PoE (802.3bt)	...	...
Power supply	48 V / 1 A (power adapter not included)	...	...
Power consumption	≤ 40 W	...	...

Main features	<ul style="list-style-type: none"> <li>• Possibility to mount on the wall or ceiling</li> <li>• Support for Reye Mesh technology</li> <li>• Number of users : 512 (max)</li> <li>• OFDMA</li> <li>• WMM (Wi-Fi Multimedia)</li> </ul> <p>Access Point is managed through the web and the cloud (Ruijie Reye application)</p> <ul style="list-style-type: none"> <li>• Load balance</li> <li>• AP placement and RF maps</li> <li>• Easy and uniform management system for many devices</li> <li>• Intuitive installation and configuration of many advanced functions</li> <li>• Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source</li> <li>• Seamless Roaming - 802.11k/v roaming function switches clients automatically to the AP with the optimal signal with a seamless transition when moving. This allows sensitive applications like VoIP and video conferences to go uninterrupted</li> </ul>	...	...
Operation temp	0 °C ... 40 °C	...	...
Permissible relative humidity	5 % ... 95 %	...	...
Weight	1.4 kg	0.05 kg	0.21 kg
Dimensions	231 x 231 x 56 mm	40 x 36 x 17 mm	1100 x 50 x 50 mm
Manufacturer / Brand	RUIJIE / REYEE	...	...
Guarantee	3 years	2 years	2 years