



	<a href="#">UPS 12V/2.1A/2.6AH/2.5 25 W 12 V DC PowerWalker</a>	<a href="#">UPS AT-UPS1200BK-LCD 1200 VA EAST</a>
		
	149.76 PLN 149.76 PLN	471.81 PLN 471.81 PLN
Nominal power	25 W	720 W
Apparent Power	—	1200 VA
Input voltage	90 ... 264 V AC	173 V ... 287 V AC
Input frequency	50 / 60 Hz	50 / 60 Hz (auto detection)
Output voltage	12 V DC $\pm$ 5 %	230 V AC $\pm$ 10 % (Approximated Sine Wave)
Connector	2.5/5.5 mm plug	...
Output frequency	...	50 / 60 Hz $\pm$ 1 %
Charging time (recover to 90% capacity)	3 hours	8 hours
Battery	3.7 V / 2.6 Ah	2 pcs - 12V/7Ah
Estimated battery operation time	<ul style="list-style-type: none"> <li>• 50 minutes - 50% load @ 1 A, 34 minutes (our tests result)</li> <li>• 25 minutes - 100% load @ 2 A, 17 minutes (our tests result)</li> </ul>	<ul style="list-style-type: none"> <li>• 57 minutes @ 100 W</li> <li>• 14 minutes @ 300 W</li> <li>• 8 minutes @ 500 W</li> </ul>
Transfer time	2 ... 6 ms	2 ... 7 ms (typical), max. 10 ms
Number of outputs	1 x 2.5/5.5 mm plug on the cable	3 pcs CEE 7/3 (Schuko)
Protections	<ul style="list-style-type: none"> <li>• Overvoltage</li> </ul>	<ul style="list-style-type: none"> <li>• Fuse</li> <li>• Overvoltage</li> <li>• Overload protection</li> <li>• Overcharge protection</li> <li>• Ethernet line filter</li> </ul>
Operation state indication	LED diodes	<ul style="list-style-type: none"> <li>• LCD display: operation mode, battery charging level, in/out voltage level,</li> <li>• Sound signaling</li> </ul>
Main features	<ul style="list-style-type: none"> <li>• Auto restart while AC is recovering</li> <li>• Power Supply Unit fault indication</li> <li>• Battery charging indication</li> </ul>	<ul style="list-style-type: none"> <li>• Auto restart while AC is recovering</li> <li>• Automatic Voltage Regulator (AVR)</li> <li>• Compatible with power generators</li> <li>• Remote management - UPSmart application included</li> <li>• Built-in EMI, RFI filter</li> <li>• Configurable alarm</li> </ul>

Application	...	<ul style="list-style-type: none"> <li>• Surveillance Systems</li> <li>• data storage centers</li> <li>• network, servers, workstations</li> <li>• Industrial Equipment</li> </ul>
Housing type	...	Tower
Operation temp. / Relative humidity	...	0 °C ... 40 °C / 20 ... 90 %
Weight	0.21 kg	8.57 kg
Dimensions	108 x 77 x 45 mm	348 x 173 x 140 mm
Manufacturer / Brand	PowerWalker	EAST
Guarantee	2 years	2 years