




	ACCESS CONTROLLER WITH FACE RECOGNITION + READER ATLO-FR-601	EXTENDER EXT-POE3H IN A HERMETIC CASING PULSAR	SWITCH POE APTI-POE0402-60W-V2 4-PORT
			
	199.00 PLN 199.00 PLN	279.00 PLN 279.00 PLN	144.00 PLN 144.00 PLN
LAN ports	6 x RJ45 (4 x IEEE 802.3af)
Face recognition distance	0.5 m ... 1 m (max 1000 faces in the database)
Management	—
Standards	...	PoE : 802.3af/at - Port PoE OUT 1/2, Passive PoE - Port PoE OUT 3	...
RFID proximity reader built-in	Unique EM 125kHz - Number of supported proximity cards : 10 000
Input voltage	...	42 ... 57 V DC	...
LED diodes	LAN, WAN, PoE
Fingerprint reader built-in	Memory of 600 fingerprint patterns
Output voltage	...	42 ... 57 V DC	...
Range of IR illumination	5 m
Number of inputs	...	1	...
White light LED illuminator range	—
Number of outputs	...	3	...
Video output	—
Connector	...	4 x RJ-45 socket	...
Wiegand interface	✓
Transmission speed	• 10 / 100 Mbps : 2 x Uplink, • 10 / 100 Mbps : 4 x LAN & PoE ports
RS-485 interface	—
LED indicators	...	LAN, PoE	...
Maximal output power	30 W / port PoE
Alarm inputs / outputs	0 / 1 - Relay output
Maximal total power	60 W
MAC addresses table	1k
Main features	• 2 x Port Uplink • Range PoE : 250 m - The EXTEND mode enabled • Mounts for mounting the device in the RACK 10" system

Supported data rates	...	<ul style="list-style-type: none"> • Range : 100 m - Input, 100 m - 3 x Output, • Supported data rates 10 / 100 Mbps - Fast Ethernet 	...
Certificates	CE
Main features	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera • Identification modes : Face recognition, Fingerprint, Proximity identifier Unique EM 125kHz, Any combination of the above • Wiegand 26 • LEDs and buzzer • Buzzer for acoustic signaling of some system events
Power supply	12 V DC	...	230 V AC
Operation temp	-10 °C ... 55 °C
Power consumption	<ul style="list-style-type: none"> ≤ 3.6 W (operation) ≤ 2.2 W (standby)
Output power	...	19.2 W / Port PoE OUT 1/2 , 14.4 W / Port PoE OUT 3 , max. 19.2 W (total)	...
Color	Silver + Black
Protections	...	<ul style="list-style-type: none"> • Overvoltage • Overload • Short-circuit 	...
Housing	Aluminum + Tempered glass, Vandal-proof	Plastic, hermetic	...
"Index of Protection"	IP65	IP56	...
Operation temp	-40 °C ... 60 °C
Operation temp. / Relative humidity	...	-25 ... 50 °C / 10 ... 90 %	...
Weight	0.38 kg	0.55 kg	0.65 kg
Dimensions	170 x 70 x 24 mm	198 x 148 x 80 mm	200 x 118 x 44 mm
Manufacturer / Brand	ATLO	PULSAR	APTI
Guarantee	2 years	2 years	2 years