



	<a href="#">WALL MOUNTING KIT USP-U30 FOR SOLAR PANELS</a>	<a href="#">IP SPEED DOME CAMERA OUTDOOR OMEGA-50P36-12-AI - 5 Mpx 4.6 ... 165 mm</a>
		
	98.78 PLN 98.78 PLN	1678.40 PLN 1678.40 PLN
Material	Aluminum	...
Standard	...	TCP/IP
Sensor	...	1/2.8 " Sony CMOS IMX335
Tilt angle adjustment:	15 ° ... 50 °	...
Matrix size	...	5 Mpx
Main features	Maximum power of the mounted panel : 80 W	...
Resolution	...	2592 x 1944 - 5 Mpx , 2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Lens	...	4.6 ... 165 mm
View angle	...	• 61 ° ... 1.9 ° (manufacturer data) • 53 ° ... 3.2 ° (our tests result)
Optical zoom	...	x 36
Auto IR illuminator	...	Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions
Range of IR illumination	...	120 m
Video output	...	—
Rotation speed (manual control)	...	• 1 °/s ... 200 °/s (horizontal) • 1 °/s ... 100 °/s (vertical)
Horizontal rotation range	...	360 ° continuous
Vertical rotation range	...	0 ° ... 93 °
Audio	...	• Microphone built-in • Audio transmission via network
RS-485 interface	...	—
Number of presets	...	255
Horizontal scan	...	✓
Image compression method	...	H.265+ / H.265 / H.264+ / H.264
Protections	...	Overvoltage
Alarm inputs / outputs	...	—
Network interface	...	10/100 Base-T (RJ-45)

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Network protocols	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
Main stream frame rate	...	<ul style="list-style-type: none"> <li>• 20 fps @ 5 Mpx</li> <li>• 25 fps @ 4 Mpx</li> </ul>
WEB Server	...	Built-in
ONVIF	...	✓
Mobile phones support	...	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">BitVision</a></li> <li>• iOS (iPhone): Free application <a href="#">BitVision</a></li> </ul>
Default IP address	...	192.168.1.168
Default admin user / password	...	admin / admin The administrator password should be set at the first start
Web browser access ports	...	80
Port ONVIF	...	8999
RTSP URL	...	rtsp://ip_address/1/h264major - Main stream rtsp://ip_address/1/h264minor - Sub stream
Route settings	...	8
OSD menu	...	preset 95



Main features	...	<ul style="list-style-type: none"> <li>• Intelligent image analysis : Intelligent Object Tracking - optimal distance : 5 ... 45 m, speed: 3 ... 12 kmph, intrusion, motion detection based on human detection, video tampering</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time</li> <li>• ICR - Movable InfraRed filter</li> <li>• BLC - configurable Back Light Compensation</li> <li>• Auto White Balance</li> <li>• IR illuminator optimization</li> <li>• Mirror - Mirror image</li> <li>• Privacy zones - max. 4</li> </ul>
Power supply	...	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 12 V DC / 3 A (power adapter included)</li> </ul>
Power consumption	...	≤ 26 W
Housing	...	Speed Dome, Metal
Color	...	White + Black
"Index of Protection"	...	IP66
Operation temp	...	-40 °C ... 60 °C
Weight	0.94 kg (total)	2.82 kg (with bracket)
Dimensions	310 x 300 x 43 mm - each item	204 x 395 x 327 mm (with bracket)
Supported languages	...	Polish, English, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand	...	OMEGA
Guarantee	2 years	2 years