



	ACCESS POINT WITH ANTENNA SXTG-5HPACD-SA MIKROTIK	EXTENDER HDMI-EX-4
		
	606.75 PLN 606.75 PLN	200.00 PLN 200.00 PLN
Frequency range	5745 MHz ... 5825 MHz	...
Antenna type	13 dBi Integrated, 2Tx 2Rx MIMO	...
Supported HDMI resolutions	...	1080p, 1080i, 720p, 576p, 576i, 480p, 480i
Standards	IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n	...
Baud rates	866 Mbps	...
LAN ports	1 x 10/100/1000 Mbps	...
Vertical beam width (V)	90 °	...
Horizontal beam width (H)	90 °	...
Operation modes	Access Point, Access Point WDS, Sector Access Point, Client, WDS client, Router or Bridge - 4 The level of license MikroTik RouterOS	...
Protections	Overvoltage protection	...
Maximal transmission range	...	<ul style="list-style-type: none"> • 40 m @ 720p / 1080p - UTP cat. 6 (manufacturer data) • 60 m @ 1080p - UTP cat. 6 (our tests result) • 50 m @ 1080p - UTP cat. 5e (our tests result)
Transmitter power	30 dBm	...
Memory	128 MB RAM, 128 MB NAND	...
Processor	QCA9882 720 MHz	...
Port USB	2.0	...
Supported audio formats	...	DTS-HD, Dolby true HD, LPCM7.1, AC3, DTS, DSD
Power supply PoE	✓	...
Power supply	<ul style="list-style-type: none"> • 15 V ... 60 V DC PoE (the set includes a power supply with 2.1/5.5mm connector and a compatible PoE power adapter) • PoE (802.3af/at) 	5 V DC / 1000 mA - 2 pcs of power adapters included
Power consumption	12 W	...

Permissible relative humidity	...	5 % ... 90 %
Operation temp	-30 °C ... 80 °C	-10 °C ... 55 °C
Weight	0.292 kg	0.045 kg
Dimensions	Ø 140 x 66 mm	67 x 56 x 22 mm
Manufacturer / Brand	MikroTik	...
Guarantee	2 years	2 years