



	ACCESS CONTROLLER MODULE MC16-PAC-EX-1 ROGER	ACCESS CONTROLLER MODULE MC16-PAC-ST-3 ROGER
		
	1400.00 PLN 1400.00 PLN	1750.00 PLN 1750.00 PLN
Number of served transitions	1	3 (two-way)
Inputs	8	...
Number of supported readers	...	12
Outputs	8	...
Number of users	max. 12000 - Number of identifiers	unlimited (purchase of the appropriate license required)
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	8 - Proximity card, PIN code, fingerprint, etc.
Number of permissions per ID	100	...
Buffer memory	8 000 000 events buffer	8 000 000 events buffer
MCT readers support	16 pcs	...
Readers connections	4 pcs - Wiegand / PRT	...
Number of login points	2	...
Number of access terminals	4	...
Number of access zones	2	6
Number of alarm zones	2	6
Number of automation nodes	2	...
Battery backup support	12 V / 7 Ah	12 V / 7 Ah
Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger) 	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface

Main features	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems) 	<ul style="list-style-type: none"> • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Operation temp	5 °C ... 40 °C	5 °C ... 40 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)	10 % ... 95 % (non-condensing)
Weight	0.14 kg	0.14 kg
Dimensions	175 x 72 x 30 mm	175 x 72 x 30 mm
Manufacturer / Brand	ROGER	ROGER
Guarantee	3 years	3 years