




	PROBE FOR FLOODING WITH WATER FPX-1-BR FOR THE AXD-200 UNIVERSAL DETECTOR SATEL	NVR NVR5232-EI 32 CHANNELS WizSense DAHUA	NVR DS-7632NXL-K2 32 CHANNELS ACUSENSE Hikvision
			
	19.00 PLN 19.00 PLN	3393.00 PLN 3393.00 PLN	2115.00 PLN 2115.00 PLN
Detection	Water
Standard	...	TCP/IP	TCP/IP
Length of the sensor cable	3 m
Sensitivity adjustment	—
Supported resolutions	...	max. 32 Mpx	max. 12 Mpx - 4000 x 3000 px
Alarm signaling	—
Relay contacts rating (resistive load)	—
Video outputs	...	1 pcs HDMI 4K 1 pcs VGA	1 pcs HDMI 4K 1 pcs VGA There is a possibility to configure a SPOT function on one of the output
Main features	• detecting the presence of water in spaces where there is a risk of leakage
Color	Brown
Audio support	...	• 32 Channels - Audio from cameras • Bi-directional audio streaming support	• 32 Channels - Audio from cameras • Bi-directional audio streaming support
Audio inputs	...	1 pcs CINCH	1 pcs CINCH
Audio outputs	...	1 pcs CINCH	1 pcs CINCH
Image compression method	...	Smart H.265+ / H.265 / Smart H.264+ / H.264 / MJPEG	H.265+ / H.265 / H.264 / H.264+
Bitrate	...	max. 384 Mbps	max. 256 Mbps
Supported hard drives	...	2 x 16 TB SATA	2 x 10 TB SATA
Recording modes	...	Manual, Sensor, Motion detection, Schedule	Manual, Sensor, Motion detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	• Records searching: by time and events type. Records playback: forward, backward, fast, slow • Advanced searching (to the one second accuracy) • Smart Playback function • Records playback from max. 32 channels in the same time @ 1080p (without AI) • Records playback from max. 24 channels in the same time @ 1080p (AI)	Records searching: by time and events type. Records playback: forward, backward, fast, slow All channels synchronous playback, Smart Search function Smart Playback function Records playback from max. 16 channels in the same time
Network interface	...	1 x RJ-45 10/100/1000 Base-TX	1 x RJ-45 10/100/1000 Base-TX
Network functions	...	Full support via network, Remote records copying, Web-Server built-in	• Live image view, Playback the records, Backup the records • max. 128 on-line users - iVMS-4200 application
Network protocols	...	HTTP, HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, SNMP, NTP, DHCP, DNS, SMTP, UPnP, IP Filter, PPPoE, FTP, DDNS, Alarm Server, IP Search, Multicast, P2P, Auto Register	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS
ONVIF	...	2.1.2	✓
Default IP address	...	192.168.1.108	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Web browser access ports	...	80, 37777	80, 8000
PC client access ports	...	37777	8000
Mobile client access ports	...	37777	8000
RTSP URL	...	• rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 • Main stream • rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 • Sub stream	• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ • Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ • Sub stream
USB	...	• 1 pcs USB 2.0 • 1 pcs USB 3.0	2 pcs USB 2.0
Serial ports	...	RS-485, RS-232	—
Alarm inputs / outputs	...	4 / 2	4 / 1

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

PTZ control	...	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 - PELCO-D/P and others 	✓
Switch PoE	—
Motion Detection	...	✓	✓
Intelligent image analysis	...	✓	✓
Main features	...	<ul style="list-style-type: none"> • Intelligent image analysis : crossing the line (tripwire), intrusion, face detection • SMD PLUS - searching for an object classified as: human, motor vehicle • Filtering of false alarms based on the recognition of persons and vehicles • Face recognition • Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask) • Support for up to 20 face databases, including 20 000 face images • In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number • Intelligent face search by metadata of different targets or uploading pictures of faces to the device and comparing them with recorded faces by similarity • Privacy zones • Cooperation with POS (Point of Sale) terminals <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR • Authorized and unauthorized license plate lists: up to 20 000 records • counting people / vehicles • crowd gathering estimation • heat map • metadata handling - automatic photo taking and collection of information enabling the subsequent identification of people and vehicles that triggered the alarm (clothing, silhouette, face, features of motor and non-mechanical vehicles) 	<ul style="list-style-type: none"> • Smart motion detection (with recognizing people and vehicles) • Filtering of false alarms based on the recognition of persons and vehicles • face detection • Comparison of faces with images from the database • Support for up to 16 face databases, including 20 000 face images • Smart search for a person based on a face photo • NVR from the AcuSense series
Mouse support	...	✓	✓
IR remote controller in the set	...	—	—
Power supply	—	12 V DC / 4 A (power adapter included)	12 V DC / 3.33 A (power adapter included)
Power consumption	...	max. 10 W (without HDD)	max. 15 W (without HDD)
Operation temp	...	-10 °C ... 55 °C	-10 °C ... 55 °C
Weight	0.05 kg	1.53 kg	1.72 kg
Dimensions	34 x 14 x 7.5 mm	375 x 284 x 55 mm	380 x 322 x 52 mm
SAP Code	303616125
Supported languages	...	Polish, English, Bulgarian, Czech, Finnish, Greek, Romanian, Serbian, Slovenian, Hungarian	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian
Manufacturer / Brand	SATEL	DAHUA	Hikvision
Guarantee	2 years	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00