



	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR APTI-XB0401HS-4KS5 4 CHANNELS	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR IDS-7204HUHI-M1/S/A 4 CHANNELS Hikvision
		
	422.40 PLN 422.40 PLN	1084.00 PLN 1084.00 PLN
Standard	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Video inputs	4 pcs BNC	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Video outputs	<ul style="list-style-type: none"> • 1 pcs HDMI • 1 pcs VGA • 1 pcs BNC 	<ul style="list-style-type: none"> 1 pcs HDMI 1 pcs VGA 1 pcs CVBS - BNC socket
Audio inputs	<ul style="list-style-type: none"> • 4 - Audio support via coaxial cable • 4 pcs CINCH 	4 pcs CINCH, Coaxial audio - Audio from cameras
Audio outputs	1 pcs CINCH	1 pcs CINCH
Image compression method	H.265+ / H.265 / H.264+ / H.264	H.265+ / H.265 / H.264 / H.264+
Image records resolutions	<ul style="list-style-type: none"> • AHD / HD-TVI : 8 Mpx - 3840 x 2160 px, 4K UHD, 5 Mpx - 2592 x 1944 px, 4 Mpx - 2560 x 1440 px, 3 Mpx - 2048 x 1536 px, 1080p - 1920 x 1080 px, 720p - 1280 x 720 px, • HD-CVI : 8 Mpx - 3840 x 2160 px, 4K UHD, 4 Mpx - 2560 x 1440 px, 1080p - 1920 x 1080 px, 720p - 1280 x 720 px, • CVBS : 960H - 960 x 576 px, • IP : max. 8 Mpx - 3840 x 2160 px 	<ul style="list-style-type: none"> • HD-TVI : 8.3 Mpx 4K UHD - 3840 x 2160 1 CH only , 8M-N - 1920 x 2160 2,3,4 CH only , 5 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 3 Mpx - 1920 x 1536 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • AHD : 5 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • HD-CVI : 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • PAL : 960H - 960 x 576 , • IP : max. 8 Mpx - 3840 x 2160

Recording speed adjustment	8 Mpx IP @ 1 ... 25 fps 8 Mpx @ 1 ... 8 fps 5 Mpx @ 1 ... 12 fps 4 Mpx @ 1 ... 15 fps 3 Mpx @ 1 ... 18 fps 1080p @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel	8 Mpx IP @ 1 ... 25 fps 8 Mpx @ 1 ... 8 fps 8M-N @ 1 ... 15 fps 5 Mpx @ 1 ... 12 fps 4 Mpx @ 1 ... 15 fps 3 Mpx @ 1 ... 18 fps 1080p @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel
Operation modes	<ul style="list-style-type: none"> • 4 x AHD / HD-CVI / HD-TVI / CVBS + 4 x IP max. 8.3 Mpx • 2 x AHD / HD-CVI HD-TVI CVBS + 7 x IP max. 8.3 Mpx • 16 x IP max. 8.3 Mpx All modes allow for any combination of the AHD, HD-CVI, HD-TVI, CVBS cameras	4 x HD-TVI / AHD / HD-CVI / CVBS / IP + 4 x IP
Recording modes	Motion Detection, Schedule	Manual, Sensor, Motion detection, Schedule
Supported hard drives	1 x 8 TB SATA	1 x 10 TB SATA
External storage devices backup	Records backup at (.avi) format to USB (pendrive)	Backup to USB drive (pendrive, external drive)
Searching and playback the records	Records searching: timeline or file list. Playback: forward, backward, fast, slow. Records playback from max. 4 channels in the same time	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 4 cameras in the same time
Network interface	...	1 x RJ-45 - 10/100 Base-TX
Bitrate	...	32 ... 10240 kbps
Network functions	<ul style="list-style-type: none"> • Network Client Software (iVMS320): live view, playback and backup of the records • IE, MS Edge, Google Chrome, Firefox, Safari browser: live view, device configuration 	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols	...	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF
Country of origin	China	...



Mobile phones support	Port no.: 6000 or access by a cloud (P2P) • Android: Free application BitVision , Android: Free application iVMS320 • iOS (iPhone): Free application BitVision , iOS: Free application iVMS320	Port no.: 8000 or access by a cloud (P2P) Android: Free application iVMS-4500 or Hik-Connect iOS (iPhone): Free application iVMS-4500 or Hik-Connect
Default IP address	192.168.1.88	DHCP or 192.168.1.64
Default admin user / password	admin / 12345	admin / - The administrator password should be set at the first start
Web browser access ports	80, 5000, 554	80
PC client access ports	80, 5000, 554	554 RTSP, 8000
Mobile client access ports	80, 5000, 6000	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Alarm inputs / outputs	4 / 1	4 / 1
PTZ control	Pelco-D, Pelco-P	<ul style="list-style-type: none"> • Control compatible with coax HD-TVI Hikvision • RS-485 - PELCO-D/P
Motion Detection	Split the screen into zones : 22 x 18 motion zones	Split the screen into zones : 22 x 18 motion zones
USB	3 pcs USB 2.0	2 x USB 2.0
Mouse support	✓	✓
IR remote controller in the set	—	✓
Main features	...	<ul style="list-style-type: none"> • DVR from the AcuSense series • Intelligent image analysis : crossing the line (tripwire), intrusion, Deep Learning technology • Smart motion detection (with recognizing people and vehicles) • Filtering of false alarms based on the recognition of persons and vehicles
Power supply	12 V DC / 2 A (power adapter included)	12 V DC / 1.5 A (power adapter included)
Color	Black	Black
Weight	0.80 kg	1.19 kg
Dimensions	260 x 242 x 46 mm	315 x 250 x 45 mm
Supported languages	Polish, English, Bulgarian, Czech, French, Spanish, German, Portuguese, Russian, Turkish, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand	APTI	Hikvision
SAP Code	...	300224953

Guarantee	2 years	3 years
-----------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00