




	<a href="#">MULTI-SOCKET PLUG WITH SWITCH MCE-142 3680 W MACLEAN ENERGY</a>	<a href="#">IP SPEED DOME CAMERA OUTDOOR IPC6624SR-X33-VF LightHunter - 4 Mpx 4.5 ... 148.5 mm UNIVIEW</a>
		
	13.76 PLN 13.76 PLN	8159.25 PLN 8159.25 PLN
Standard	...	TCP/IP
Rated voltage	230 V / 50 Hz	...
Maximal total load	3680 W	...
Sensor	...	1/2.8 " Progressive Scan CMOS
Total maximal current	16 A	...
Matrix size	...	4 Mpx
Resolution	...	2688 x 1520 - 4 Mpx
Number of outlets	<ul style="list-style-type: none"> <li>• 1 pcs 2P+Z,</li> <li>• 2 pcs 2P - flat</li> </ul>	...
Lens	...	4.5 ... 148.5 mm
Grounding	✓	...
View angle	...	51 ° ... 2.5 °
Main features	Switch built-in - with light indication	...
Optical zoom	...	x 33
Digital zoom	...	x 16
Range of IR illumination	...	150 m
Video output	...	✓
Preset rotation speed	...	<ul style="list-style-type: none"> <li>• 300 °/s (horizontal)</li> <li>• 240 °/s (vertical)</li> </ul>
Rotation speed (manual control)	...	<ul style="list-style-type: none"> <li>• 0.1 °/s ... 200 °/s (horizontal)</li> <li>• 0.1 °/s ... 200 °/s (vertical)</li> </ul>
Horizontal rotation range	...	360 ° - continuous
Vertical rotation range	...	-15 ° ... 90 °
RS-485 interface	...	✓
Number of presets	...	1024
Horizontal scan	...	✓
Route settings	...	16
Image compression method	...	Ultra H.265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	2 / 1
Audio	...	<ul style="list-style-type: none"> <li>• External microphone input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Audio detection</li> </ul>
Main stream frame rate	...	25 fps @ 4 Mpx
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in

Max. number of on-line users	...	32
ONVIF	...	✓
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>
Default IP address	...	DHCP or 192.168.1.13
Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream



Main features	...	<ul style="list-style-type: none"> <li>• Intelligent Object Tracking</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• Configurable Privacy Zones - 24</li> <li>• Motion Detection</li> <li>• Tamper signaling</li> <li>• Image rotation and mirror</li> <li>• Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions</li> <li>• Home Position - set the camera to the specified position if no operator activity for a specified dwell time</li> <li>• Overvoltage protection : 6 kV</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, crowd gathering estimation, people counting</li> </ul>
Power supply	...	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 24 V DC / 2.5 A (power adapter included),</li> <li>• 24 V AC</li> </ul>
Power consumption	...	≤ 25 W
Housing	Plastic	Speed Dome, Metal
Color	White	White
Operation temp	...	-40 °C ... 70 °C
"Index of Protection"	...	IP66
Vandal-proof	...	—
Weight	0.1 kg	5.31 kg
Dimensions	95 x 72 x 55 mm	Ø 227 x 385 mm

Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian
Manufacturer / Brand	MACLEAN ENERGY	UNIVIEW
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00