




	<a href="#">CABLE EURO-W/4CINCH-1.2 1.2 m</a>	<a href="#">ACCESS CONTROLLER ASC2104B-T DAHUA</a>	<a href="#">ACCESS CONTROLLER ASC2204C-H DAHUA</a>
			
	3.18 PLN 3.18 PLN	822.00 PLN 822.00 PLN	3173.00 PLN 3173.00 PLN
Number of served transitions	...	4 (two-way)	4 (one-way)
Support	...	DAHUA ASC2204C-H	DAHUA
Number of supported readers	...	4 pcs	4 pcs
Cable	EURO Plug / 4 x CINCH Plug	...	...
Battery backup support	...	—	max. 7 Ah
Input lines	...	...	20 pcs
Length of the cable	1.2 m	...	...
Output lines	...	5 pcs - Relay	12 pcs - Relay
Alarm inputs / outputs	...	1 / 1	...
Communication	...	<ul style="list-style-type: none"> <li>• RS-485,</li> <li>• Wiegand 34/26,</li> <li>• Control panel CAN (Controler Area Network)</li> </ul>	<ul style="list-style-type: none"> <li>• RS-485,</li> <li>• Ethernet,</li> <li>• Wiegand 34/26</li> </ul>
Power supply	...	12 V DC / 1 A	80 ... 260 V AC
Application of respective connectors	<ul style="list-style-type: none"> <li>• White : Input Video</li> <li>• Red : Output Video</li> <li>• Black : Input AUDIO</li> <li>• Blue : Output AUDIO</li> </ul>	...	...

Main features	<ul style="list-style-type: none"> <li>• Very easy and quick assembly</li> </ul>	<ul style="list-style-type: none"> <li>• 20 000 indexed users</li> <li>• History of 30 000 events</li> <li>• Function to prevent of multiple use of the same code/card to gain access (anti-passback)</li> <li>• Door Left Open and Door Forced Open alarms</li> <li>• Watchdog built-in</li> <li>• Possibility to mount on a wall, or on the DIN TS-35 rail</li> </ul>	<ul style="list-style-type: none"> <li>• Support for 4 doors (20 inputs: 4x lock state, 4x door sensor, 4x exit button, 8x alarm line)</li> <li>• 200000 indexed users</li> <li>• History of 150000 events</li> <li>• Possibility to connecting in cascade</li> <li>• 128 General Purpose Schedules</li> <li>• Function to prevent of multiple use of the same code/card to gain access (anti-passback)</li> <li>• Door Left Open and Door Forced Open alarms</li> <li>• Tamper detection - opening the enclosure</li> <li>• Watchdog built-in</li> <li>• Remote programming from PC</li> <li>• Real time clock with battery backup</li> <li>• Metal housing</li> <li>• ONVIF compliance</li> </ul>
Operation temp	...	-30 °C ... 60 °C	-30 °C ... 60 °C
Permissible relative humidity	...	max. 95 % (non-condensing)	max. 95 % (non-condensing)
Weight	0.140 kg	0.384 kg	2.77 kg
Dimensions	...	209 x 117 x 51 mm	270 x 330 x 90 mm
Manufacturer / Brand	...	DAHUA	DAHUA
Guarantee	2 years	3 years	3 years