



	IP CAMERA IPC-T22AP - 1080p 2.8 mm	SWITCH DISCONNECTOR WITH FUSE LE-606619 ONE-PHASE 63 A D02 LEGRAND
		
	99.00 PLN 99.00 PLN	68.16 PLN 68.16 PLN
Standard	TCP/IP	...
Device type	...	One-phase
Rated current	...	63 A
Sensor	1/2.8 " Progressive Scan CMOS	...
Number of poles	...	1
Matrix size	2.1 Mpx	...
Rated voltage	...	230 / 400 V AC
Resolution	1920 x 1080 - 1080p	...
Rated insulation voltage	...	500 V
Lens	2.8 mm	...
Rated impulse withstand voltage	...	6000 V
View angle	102 °	...
Fusing characteristics	...	—
Range of IR illumination	30 m	...
Type (size)	...	D02
Audio	—	...
Breaking capacity	...	50000 A AC
Connectors type	...	cable terminals
Image compression method	H.265 / H.264	...
Wire gauge	...	2.5 ... 25 mm ²
Main stream frame rate	25 fps @ 1080p	...
Environment class	...	II
Network protocols	TCP, DHCP	...
ONVIF	✓	...
Housing	...	Plastic, TH-35 rail mounting
Width in 17.5 mm modules	...	1.5
Network interface	Ethernet : 100 Mbps	...
WEB Server	—	...
Operation temp	...	-26 °C ... 60 °C

Mobile phones support	Access by a cloud (P2P) • Android: Free application IMOU • iOS (iPhone): Free application IMOU	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	DHCP	...
Web browser access ports	—	...
PC client access ports	—	...
Mobile client access ports	—	...
Port ONVIF	—	...
RTSP URL	—	...
Memory card slot	—	...
Main features	• Motion Detection • People detection • D-ZOOM - Digital Zoom : 16x	...
Power supply	PoE	...
Power consumption	< 3.6 W	...
"Index of Protection"	IP67	...
Weight	0.21 kg	0.162 kg
Dimensions	Ø 110 x 101 mm	83 x 70.3 x 26.5 mm
Supported languages	—	...
Manufacturer / Brand	DAHUA	LEGRAND
Guarantee	2 years	2 years