



	<a href="#">SWITCH POE CS4010-8ET-110 8-PORT DAHUA</a>	<a href="#">POE SWITCH / EXTENDER PFT1320 3-PORT</a>
		
	746.00 PLN 746.00 PLN	75.20 PLN 75.20 PLN
LAN ports	<ul style="list-style-type: none"> <li>• 8 x RJ45 10/100 Base-T ( 1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 10/100/1000 Base-T - Uplink</li> </ul>	<ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at),</li> <li>• 2 x RJ45 10/100 Base-T + PoE (802.3af)</li> </ul>
Transmission speed	<ul style="list-style-type: none"> <li>• 10 / 100 Mbps : 8 LAN &amp; PoE ports,</li> <li>• 10 / 100 / 1000 : 2 Uplink ports</li> </ul>	10 / 100 Mbps
Maximal output power	<ul style="list-style-type: none"> <li>• 90 W / port Hi-PoE / PoE 802.3bt - Port 1</li> <li>• 30 W / port PoE 802.3af/at - 2 ... 8 ports</li> </ul>	15.4 W @ port PoE - First device
Maximal total power	110 W	...
MAC addresses table	8k	...
Management	✓	—
Range	...	100 m - Input 100 m - Output
Operation modes	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6	...
Operation temp. / Relative humidity	...	-30 ... 65 °C / 10 ... 90 %
LED diodes	Power, System, PoE, Link/Act	Link, Act

Main features	<ul style="list-style-type: none"> <li>• Switch is managed through the web and the cloud (DoLynk Care application)</li> <li>• PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-)</li> <li>• Intelligent management of Power Supply Unit power's output stage</li> <li>• protection against lightning discharges and voltage differences and strokes between devices</li> <li>• Watchdog PoE</li> <li>• Loop Protection</li> <li>• Compliance with the LLDP protocol</li> <li>• Spanning Tree STP/RSTP</li> <li>• Port Based VLAN : 32</li> <li>• Data Flow Control (802.3x)</li> <li>• DHCP client</li> <li>• RESET button</li> <li>• Possibility to mount to the wall</li> </ul>	<ul style="list-style-type: none"> <li>• Possibility to connecting in cascade</li> <li>• The device can function as a LAN network and PoE power extender</li> </ul>
Certificates	CE	...
Protections	<ul style="list-style-type: none"> <li>• Protection against lightning discharges (common/differential) : 4 / 2 kV</li> <li>• Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV</li> </ul>	—
Housing	Desktop, Metal	Plastic
Power supply	54 V DC / 2.22 A (power adapter included)	PoE (802.3af/at)
Power consumption	max. 110 W	0.3 W
Operation temp	-10 °C ... 55 °C	...
Weight	0.49 kg	0.05 kg
Dimensions	190 x 106 x 30 mm	88 x 44 x 22 mm
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years