



|   | <a href="#">VIDEO BALUN TR-1RJ-<br/>HD*P2</a>  | <a href="#">SINGLE-MODE MODULE<br/>GTS-SFP-LH-SMD</a>                              |
|---|--|--|
|   |   |  |
|   | 19.73 PLN<br>19.73 PLN   | 27.04 PLN<br>27.04 PLN   |
| Transmission protocols                  | ...  | IEEE 802.3z 1000Base-FX  |
| In package                              | <b>2 pcs The price for package</b>   | ...  |
| Fiber type                              | ...  | 8.3/125 μm, 8.7/125 μm, 9/125 μm, 10/125 μm - Single-mode fiber                    |
| Maximal transmission range              | ...  | 20 km  |
| Transfer rate                           | ...  | 1.25 Gb/s / 1.063 Gb/s   |
| Number of used fibers                   | ...  | 2  |
| Optical connectors                      | ...  | 2 x LC / PC  |
| Light source / optical wavelength       | ...  | Laser FP / 1310 nm   |
| Transmitter power                       | ...  | -9 ... -3 dB   |
| Receiver sensitivity                    | ...  | ≥ -23 dB   |
| Standard                                | <ul style="list-style-type: none"> <li>• AHD - 8 Mpx 4K UHD,</li> <li>• HD-CVI - 8 Mpx 4K UHD,</li> <li>• HD-TVI - 8 Mpx 4K UHD,</li> <li>• CVBS - PAL, NTSC</li> </ul>  | ...  |
| Power supply                            | ...  | 3.3 V DC   |
| Device type                             | Passive  | ...  |
| Number of channels                      | 1 Video, 1 DC  | ...  |
| Coaxial socket voltage range 75Ω (CVBS) | 1 Vpp  | ...  |
| Video transmission range                | <ul style="list-style-type: none"> <li>• 250 m @ 720p - UTP cat. 5e</li> <li>• 150 m @ 1080p - UTP cat. 5e</li> <li>• 400 m @ CVBS - PAL, NTSC - UTP cat. 5e</li> </ul>  | ...  |
| Attenuation                             | <ul style="list-style-type: none"> <li>• 4.43 MHz @ 0.64 dB</li> <li>• 11 MHz @ 0.85 dB</li> <li>• 21 MHz @ 1.09 dB</li> <li>• 38 MHz @ 1.19 dB</li> <li>• 42 MHz @ 1.23 dB</li> <li>• 67.5 MHz @ 2.06 dB</li> </ul> | ...  |
| Symmetrical socket impedance            | 100 Ω  | ...  |
| Connectors type                         | Video - BNC Plug with cable<br>Power supply - Socket / Plug<br>2.1/5.5 mm  | ...  |

|                               |   |                |
|-------------------------------|---|----------------|
| Symmetrical socket type       | RJ-45 (8-pin, 4 pairs) Socket   | ...            |
| Permissible relative humidity | < 95 %  | ...            |
| Operation temp                | -50 °C ... 55 °C  | 0 °C ... 70 °C |
| Power supply distance         | Power supply 12V DC :<br>150 m @ 110 mA<br>100 m @ 160 mA<br>50 m @ 330 mA<br>30 m @ 550 mA | ...            |
| Weight                        | 0.030 kg  | 0.017 kg       |
| Dimensions                    | 41 x 19.3 x 19.2 mm   | ...            |
| Guarantee                     | 2 years   | 2 years        |