




| | PATCH PANEL POE-8/R19 | FLUSH BOX PK-60/K-G/EPN Elektro-Plast | POE ADAPTER ASDC-12-121-HS ATTE |
|-------------------------------------|---|--|--|
| |  |  |  |
| | 181.69 PLN 181.69 PLN | 2.98 PLN 2.98 PLN | 79.00 PLN 79.00 PLN |
| Output power | ... | ... | max. 12 W |
| Number of inputs | 8 pcs (RJ-45) | ... | 1 pcs RJ-45 |
| Number of sections | ... | 1 | ... |
| Number of outputs | 8 pcs (RJ-45) | ... | ... |
| "Index of Protection" | ... | — | ... |
| Maximal output current | 550 mA / Output | ... | ... |
| Input voltage | ... | ... | 35 ... 56 V DC - PoE |
| Output voltage | max. 60 V | ... | 12 V DC - 2.1/5.5 mm plug on the cable |
| Material | ... | Plastic | ... |
| Montage hole diameter | ... | Ø 68 mm | ... |
| Main features | Pin numbers for RJ-45 connector <ul style="list-style-type: none"> • DATA 1, 2 and 3, 6 • Power supply 4, 5 (+) and 7, 8 (-) • Supported data rates 10 / 100 Mbps • Maximal load for single port 550 mA | <ul style="list-style-type: none"> • Flush-mounted, for hollow walls • 2 special screws with holders to fastening to the wall - included | <ul style="list-style-type: none"> • Output current : 1 A • "Index of Protection" : IP20 |
| Color | ... | Brick red | Green |
| Protections | <ul style="list-style-type: none"> • Short-circuit • Overload | ... | — |
| LED indicators | Power supply | ... | DC output voltage presence indication |
| Operation temp | ... | ... | -10 °C ... 40 °C |
| Housing | 1 U Rack 19" | ... | Plastic |
| Operation temp. / Relative humidity | -10 °C ... 55 °C / < 95 % | ... | ... |
| Weight | 0.29 kg | 0.024 kg | 0.02 kg |
| Dimensions | 483 x 44 x 36 mm | Ø 60 x 47 mm - Internal dimensions Ø 67 x 48 mm - External dimensions | 74 x 22 x 17 mm |
| Manufacturer / Brand | DELTA | Elektro-Plast | ATTE |
| Guarantee | 3 years | 2 years | 3 years |