



	CIRCUIT BREAKER HN-B25/3 THREE-PHASE 25 A B TYPE EATON	IP CAMERA IPC-CD2C40-ZS-2812 - 3.7 Mpx 2.8 ... 12 mm - MOTOZOOM DAHUA
		
	63.17 PLN 63.17 PLN	951.00 PLN 951.00 PLN
Standard	...	TCP/IP
Sensor	...	1/3 " Progressive Scan CMOS
Matrix size	...	4 Mpx
Device type	Circuit Breaker, Three-phase	...
Rated current	25 A	...
Number of poles	3	...
Tripping curves	B type	...
Breaking capacity	6000 A	...
Rated voltage	• 230 V AC / 50 Hz • 400 V AC / 50 Hz	...
Connectors type	screw terminals	...
Wire gauge	1 mm ² - 25 mm ²	...
Resolution	...	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Main features	• Contact position indicator • Possibility of sealing	...
Width in 17.5 mm modules	3	...
Lens	...	2.8 ... 12 mm - Motozoom
View angle	...	• 97 ° ... 31 ° (manufacturer data) • 86 ° ... 29 ° (our tests result)
Compression	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
S/N ratio	...	> 50 dB
Range of IR illumination	...	30 m
Alarm inputs / outputs	...	—
Bitrate	...	• 12 kbps ... 6144 kbps - H.265 • 32 kbps ... 6144 kbps - H.264
Main stream frame rate	...	20 fps @ 3.7 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	HTTP, HTTPS, TCP, ARP, RTSP, RTP, RTCP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/IPv6, QoS, UPnP, NTP, Bonjour, IEEE 802.1x, Multicast, ICMP, IGMP, TLS, SSH, Multicast
Audio	...	—
WEB Server	...	Built-in, NVR compliance
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)
Max. number of on-line users	...	20

ONVIF	...	16.12
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.108
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
RS-485 interface	...	—
Main features	...	<ul style="list-style-type: none"> • Motozoom lens • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Mirror - Mirror image • Motion Detection - max. 4 zones • Privacy zones - max. 4 • D-ZOOM - Digital Zoom : x16
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 470 mA
Power consumption	...	<ul style="list-style-type: none"> ≤ 5.6 W @ 12 V DC ≤ 6.5 W @ PoE
Housing	Plastic, DIN, TS-35 rail mounting	Dome, Metal
Color	...	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Supported languages	...	Polish, English, Czech
Weight	0.316 kg	0.39 kg
Dimensions	52.5 x 84.5 x 73 mm	Ø 122 x 89 mm
Manufacturer / Brand	EATON	DAHUA
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00