



| | PERFORATED MOUNTING RAIL A19-TS-35-C | OVERVOLTAGE LIMITER AXON-POWER/DIN |
|---|---|---|
| |  |  |
| | 56.55 PLN 56.55 PLN | 104.30 PLN 104.30 PLN |
| Rated voltage | ... | 230 V AC / 50 Hz |
| Material | Steel galvanized - DIN rail (TS-35) + Aluminum PA11 | ... |
| Maximal voltage | ... | 250 V AC / 50 Hz |
| Rated current | ... | 10 A |
| Color | Silver + Black | ... |
| Protection level Up L/PE, N/PE | ... | ≤ 1.3 kV |
| Main features | Perforated | ... |
| Protection level Up L/N | ... | ≤ 3 kV |
| Nominal discharge current (L/N, L/PE, N/PE) | ... | 4 kA - 8/20 μs |
| Maximum stroke current (L/N, L/PE, N/PE) | ... | 10 kA 8/20 μs (type 2) |
| Operation state indication | ... | ✓ |
| Connectors type | ... | 2 x terminals |
| Housing | ... | <ul style="list-style-type: none"> • Plastic • DIN, TS-35 rail mounting |
| Weight | 0.38 kg | 0.075 kg |
| Dimensions | 19 " x 1 U x 105 mm | 86 x 58 x 35 mm |
| Guarantee | 2 years | 2 years |