



	ACCESS CONTROLLER ASI1212F DAHUA	SINGLE-MODE PIGTAIL - PLUG SC PIG-SC
		
	944.00 PLN 944.00 PLN	4.03 PLN 4.03 PLN
Connector type	...	SC
Cards support	13.56 MHz S50	...
Reading distance of prox-keys	1 ... 3 cm	...
Keyboard built-in	—	...
Autonomous operation	✓	...
Fiber optic type	...	9 / 125 μm : G-652.D
Battery backup support	—	...
Length	...	1 m
Input lines	3	...
Output lines	3	...
Identification time	< 1.5 s	...
Communication	<ul style="list-style-type: none"> • RS-485 • Wiegand • LAN 	...
RS-485 interface	✓	...
RS-232 interface	—	...
Wiegand interface	✓	...
Network interface	10/100 Base-T	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
USB	—	...
Memory card slot	—	...
Internal memory	Support storage of 150 000 records	...
Power supply	12 V DC / 1 A	...

Main features	<ul style="list-style-type: none"> • Built-in LCD display 240 x 320 px - 2.8 " capacitive touch screen • Fingerprint reader built-in • Memory of 3000 fingerprint patterns • Possible connection of the external ASR series reader (read in/out door control) • Identification modes : Proximity identifier 13.56 MHz S50, Fingerprint, PIN, Any combination of the above • Remote access verification • Tamper detection - removing from mounting surface • Support for door contact and exit button • Indication of forced entry and the lack of closing doors • 30000 indexed users • Possibility to configure access groups • 128 General Purpose Schedules • 128 time periods within single Schedule • Holiday Schedules • Anti-passback • Integration with an alarm system via in/out line • Remote programming from PC 	...
"Index of Protection"	—	...
Operation temp	-10 °C ... 45 °C	...
Permissible relative humidity	5 ... 90 % (non-condensing)	...
Dimensions	115 x 115 x 32 mm	...
Weight	0.22 kg	...
Supported languages	English	...
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years

