




	ACCESS CONTROLLER MODULE MC16-PAC-ST-16 ROGER	REAR SUPPORT FOR THE MOUNTING PROFILE USP- TN-400 FOR SOLAR PANELS	SWITCHING ADAPTER LRS-100-24 MEAN WELL
			
	6430.00 PLN 6430.00 PLN	16.20 PLN 16.20 PLN	72.56 PLN 72.56 PLN
Adapter type	Switching
Material	...	Aluminum	...
Number of served transitions	16 (two-way)
Number of supported readers	64
Power voltage	85 ... 264 V AC
Number of users	unlimited (purchase of the appropriate license required)
Operating frequency	47 ... 63 Hz
Output voltage	24 V DC
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.
Buffer memory	8 000 000 events buffer
Output voltage adjustment	21.6 ... 28.8 V
Number of access zones	32
Maximal load	4.5 A
Number of alarm zones	32
Output power	108 W
Number of outputs	1 pcs
Battery backup support	12 V / 7 Ah
Protections	<ul style="list-style-type: none"> • Short-circuit • Overload • Overvoltage
Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface
Operation temp. / Relative humidity	-30 °C ... 70 °C / 20 % ... 90 %

Main features	<ul style="list-style-type: none"> • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Operation temp	5 °C ... 40 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)
Weight	0.14 kg	0.21 kg	0.31 kg
Dimensions	175 x 72 x 30 mm	400 x 35 x 35 mm	129 x 97 x 30 mm
Manufacturer / Brand	ROGER	...	MEAN WELL
Guarantee	3 years	2 years	3 years