



	POWER SUPPLY ADAPTER PFM321D-EN DAHUA	IP CAMERA IPC3615SB-ADF28KMC-I0 Tri-Guard - 5 Mpx 2.8 mm UNIVIEW
		
	46.00 PLN 46.00 PLN	1325.61 PLN 1325.61 PLN
Model identifier	PFM321D-EN	...
Standard	...	TCP/IP
Adapter type	Switching	...
Input voltage	100 - 240 V AC	...
Sensor	...	1/2.7 " Progressive Scan CMOS
Matrix size	...	5 Mpx
AC input frequency	50 / 60 Hz	...
Output voltage	12.0 V DC	...
Output voltage adjustment	—	...
Output current	1.0 A	...
Output power	12.0 W	...
Number of outputs	1 pcs	...
Power connectors type	<ul style="list-style-type: none"> • 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug 	...
Resolution	...	2880 x 1620 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
Housing type	Desktop	...
Lens	...	2.8 mm
View angle	...	<ul style="list-style-type: none"> • 101 ° (manufacturer data) • 105 ° (our tests result)
White light LED illuminator range	...	30 m
Range of IR illumination	...	30 m
S/N ratio	...	> 56 dB
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	...	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in • Audio transmission via network • Audio detection
Main stream frame rate	...	25 fps @ 5 Mpx
Network interface	...	10/100 Base-TX (RJ-45)
WEB Server	...	Built-in

Max. number of on-line users	...	32
ONVIF	...	✓
Mobile phones support	...	Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	...	DHCP or 192.168.1.13
Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream

Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • Active deterrence function - Light and sound alarm • F-DNR (Defog) - Reduction of image noise caused by precipitation • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • ROI - improve the quality of selected parts of image • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Intelligent image analysis : crossing the line (tripwire), intrusion, entering the marked area, leaving the marked area, people counting, crowd gathering estimation, face detection • Overvoltage protection : 4 kV
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 625 mA
Power consumption	...	≤ 7.5 W
Housing	...	Dome, Metal
Color	...	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.1 kg	0.42 kg
Dimensions	...	Ø 110 x 95 mm
Supported languages	...	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	DAHUA	UNIVIEW
Guarantee	3 years	3 years