



	LED FLOODLIGHT WITH MOTION SENSOR AD-NL-6153BLR4 ADVITI	IP CAMERA TC-C34XP SPEC:W/E/Y/2.8MM/V4.0 Color Maker - 4 Mpx 2.8 mm TIANDY
		
	41.96 PLN 41.96 PLN	795.00 PLN 795.00 PLN
Luminous flux	800 lm	...
Standard	...	IP
Light color	Neutral, 4000 K	...
Twilight switch	✓	...
Nominal power	10 W	...
CRI	> 80	...
Resolution	...	2592 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor	...	1/2.8 " Progressive Scan CMOS
Lens	...	2.8 mm
View angle	...	• 100 ° (manufacturer data) • 91 ° (our tests result)
White light LED illuminator range	...	15 m
Memory card slot	...	Micro SD card support up to 512GB
Image compression method	...	S+265 / H.265 / H.264
Alarm inputs / outputs	...	—
Main features	<ul style="list-style-type: none"> • LED SMD diodes • LED lifetime 25 000 h • Solid workmanship • PIR detector - Built-in, Range : 4 ... 8 m, Detection angle : 120 ° • Sensitivity adjustment of the twilight sensor and PIR • Lighting time adjustment : 10 ... 600 s • IK rating : IK08 	...
Audio	...	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network
Main stream frame rate	...	25 fps @ 4 Mpx
Operation temp	-20 °C ... 40 °C	...
Interface	...	10/100 Base-TX (RJ-45)

WEB Server	...	Built-in
Max. number of on-line users	...	2
ONVIF	...	✓
Mobile phones support	...	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus
Access from PC	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Default IP address	...	DHCP or 192.168.1.2
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports	...	3000, 3001
PC client access ports	...	3000, 3001
Port ONVIF	...	80
Intelligent image analysis	...	<ul style="list-style-type: none"> • crossing the line (tripwire) • intrusion
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • Motion Detection • Privacy zones
Power supply	230 V AC	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V / 590 mA
Power consumption	...	≤ 7 W
Housing	Aluminum	Dome - Metal + Plastic

Color	...	White
"Index of Protection"	IP65	IP66
Mechanical protection class	...	—
Operation temp	...	-40 °C ... 65 °C
Weight	0.22 kg	0.33 kg
Dimensions	105 x 127 x 75 mm	Ø 117 x 96 mm
Supported languages	...	Polish, English, Albanian, Arabic, Spanish, Korean, French, Dutch, Hebrew, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian
Manufacturer / Brand	ORNO / ADVITI	TIANDY
Guarantee	2 years	3 years