



	IP VANDALPROOF CAMERA DS-2CD1123G2-I(2.8MM) - 1080p Hikvision	IP VANDALPROOF CAMERA DS-2CD1123G0E-I(2.8mm)(C) - 1080p Hikvision
		
	572.00 PLN 572.00 PLN	572.00 PLN 572.00 PLN
Standard	TCP/IP	TCP/IP
Sensor	1/2.9 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS
Matrix size	2.1 Mpx	2.1 Mpx
Resolution	1920 x 1080 - 1080p 1280 x 720 - 720p	1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	2.8 mm	2.8 mm
View angle	<ul style="list-style-type: none"> • 104 ° (manufacturer data) • 100 ° (our tests result) 	<ul style="list-style-type: none"> • 112 ° (manufacturer data) • 105 ° (our tests result)
Range of IR illumination	30 m	30 m
S/N ratio	...	> 50 dB
RS-485 interface	...	—
Memory card slot	—	—
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	—	—
Audio	—	—
Network interface	10/100 Base-T (RJ-45)	...
Bitrate	...	32 kbps ... 8192 kbps
Main stream frame rate	25 fps @ 1080p	25 fps @ 1080p
Network protocols	...	TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, IGMP, QoS, UDP
WEB Server	Built-in	Built-in
Max. number of on-line users	6	6
ONVIF	✓	18.12
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • Configurable Privacy Zones • Mirror - Mirror image • Sharpness - sharper image outlines • Smart motion detection (with recognizing people and vehicles) 	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • BLC - configurable Back Light Compensation • Day/Night mode (color/b&w/auto) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Configurable Privacy Zones • Motion Detection • Mirror - Mirror image • Sharpness - sharper image outlines
Mobile phones support	<ul style="list-style-type: none"> • Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	<ul style="list-style-type: none"> • Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS (iPhone): Free application Hik-Connect
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
Default IP address	192.168.1.64	192.168.1.64
Web browser access ports	80	80
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	8000	8000

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Port ONVIF	80	80
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization 	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 420 mA 	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 410 mA
Power consumption	<ul style="list-style-type: none"> • ≤ 5 W @ 12 V DC • ≤ 6.5 W @ PoE (802.3af) 	<ul style="list-style-type: none"> • ≤ 6.5 W @ PoE (802.3af) • ≤ 5 W @ 12 V DC
Color	White	White
Housing	Dome, Metal + Plastic	Dome - Plastic + Metal
Vandal-proof	IK10	IK10
"Index of Protection"	IP67	IP67
Operation temp	-30 °C ... 60 °C	-30 °C ... 60 °C
Weight	0.39 kg	0.38 kg
Dimensions	Ø 111 x 85 mm	Ø 111 x 83 mm
Supported languages	Polish, English	English
Manufacturer / Brand	Hikvision	Hikvision
SAP Code	311320701	311315934
Guarantee	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00