

	POWER DISTRIBUTION UNIT PR-1.5M-4G-SW/B (4 OUTLETS) 1.3 m	LOCKABLE CASTOR A19-K-N TO RACK CABINET	PHOTOCELL FAAC-XP20WD TXRX SET
			
	19.31 PLN 19.31 PLN	11.18 PLN 11.18 PLN	474.00 PLN 474.00 PLN
Wheel diameter	...	50 mm	...
Max cabinet's weight	...	250 kg	...
Rated voltage	220 ... 240 V AC / 50 Hz	...	...
Material	...	Metal + Plastic	...
Total maximal current	10 A	...	...
Beam width	...	...	± 7 ° @ 20 m , ± 13.5 ° @ 5 m
Maximal total load	2500 W	...	...
Number of outlets	4 grounded outlets 10A/250V CEE 7/5	...	...
Operation range	...	...	• 20 m, • 10 m Battery
Fuse	—	...	...
Switch	✓	...	...
Response time	...	...	40 ms
Wire gauge	3 x 1.5 mm ²	...	...
Length of the cable	1.3 m	...	...
Power supply	...	...	• 12 ... 24 V AC/DC / Battery : 3 V CR2 (not included) Transmitter, • 12 ... 24 V AC/DC Receiver
Current consumption	...	...	• 5 mA @ 24 V DC / 40 µA Battery Transmitter • 30 mA Receiver
Number of relay outputs	...	...	1
Output	...	...	1 x NC

Main features	...	...	• Cooperation with the FAAC gate automation system • Angle adjustment range $\pm 90^\circ$ horizontal, • Wireless - 4 Channels, • Possibility to install up to 4 pairs of photocells on the same automation system • Protection from interference produced by external light sources (such as vehicle LED headlights) • Surface/column mounting • Immunity to environmental changes
Housing	Plastic	...	Plastic
"Index of Protection"	...	...	IP54
Color	Black	...	Black
Operation temp	...	...	-20 °C ... 55 °C
Weight	0.28 kg	0.31 kg	• 0.070 kg Transmitter • 0.076 Receiver
Dimensions	226 x 54 x 46 mm	...	130 x 42 x 41 mm Transmitter / Receiver
Manufacturer / Brand	...	...	FAAC
Guarantee	2 years	2 years	2 years

