




|                         | <a href="#">ACCESS POINT 4G LTE +ROUTER ALINK-MR920</a><br>2.4 GHz 300 Mbps       | <a href="#">SMART LED LIGHTING CONTROLLER SLW-01 Wi-Fi, SUPLA 12 ... 24 V DC</a><br>ZAMEL                            | <a href="#">CONNECTOR FOR LED STRIPS AD-TL-6499/Z-P-Z</a><br>8 mm ORNO              |
|-------------------------|---|--|---|
|                         |  |                                     |  |
|                         | 201.60 PLN<br>201.60 PLN  | 161.20 PLN<br>161.20 PLN   | 4.06 PLN<br>4.06 PLN  |
| Support                 | ...   | SUPLA  | ...   |
| Frequency range         | 2.4 GHz   | ...  | ...   |
| Number of power outputs | ...   | ...  | 2 pcs   |
| Strip width             | ...   | ...  | 8 mm  |
| Length of the cable     | ...   | ...  | 140 mm  |
| Application             | ...   | Works with LED lighting - (RGB) 12-24V LED strips  | Works with LED lighting   |
| Antenna type            | 2 x Omnidirectional antenna<br>Wi-Fi - 8 dBi, 4G LTE                              | ...  | ...   |
| Rated voltage           | ...   | 12 ... 24 V DC   | ...   |
| Maximal power voltage   | ...   | ...  | 48 V  |
| Maximal total load      | ...   | 140 W  | ...   |
| Standards               | IEEE 802.11 b/g/n, 4G LTE,<br>3G  | ...  | ...   |
| Total maximal current   | ...   | 6 A ( 2 A / Channel )  | ...   |
| Baud rates              | 11n : 300 Mbps<br>11g : 54 Mbps<br>11b : 11 Mbps<br>LTE : 150 / 50 Mbps           | ...  | ...   |
| Maximal outputs load    | ...   | LED RGB 12 V : 5 m - 70 W<br>LED RGB 24 V : 10 m -<br>140 W  | ...   |
| Number of inputs        | ...   | 1  | ...   |
| Number of outputs       | ...   | 3  | ...   |
| Connector type          | ...   | screw terminals  | ...   |
| LAN ports               | • 1 x 10/100 Mbps -<br>LAN/WAN<br>• 2 x 10/100 Mbps - LAN                         | ...  | ...   |
| Wireless                | ...   | Wi-Fi, 2.4 GHz - IEEE 802.11<br>b/g/n  | ...   |
| Mobile phones support   | ...   | • The <a href="#">SUPLA</a> free<br>application on Android<br>• The <a href="#">SUPLA</a> free<br>application on iOS | ...   |
| Receiver sensitivity    | • 11g 54M : -74 dBm<br>• 11n HT20 MCS7 : -71 dBm<br>• 11n HT40 MCS7 : -67 dBm     | ...  | ...   |

|                               |   |   |                 |
|-------------------------------|---|---|-----------------|
| Transmitter power             | < 27 dBm @ 2.4 GHz  | ...   | ...             |
| LED indicators                | Power, WAN, WLAN, LAN, GSM  | ...   | ...             |
| Housing                       | ...   | Plastic   | Plastic         |
| "Index of Protection"         | ...   | IP20  | —               |
| Color                         | ...   | Green   | White           |
| Network type                  | <ul style="list-style-type: none"> <li>• 4G : FDD-LTE B1/B3/B7/B8/B20/B28 - 2100 / 1800 / 2600 / 900 / 800 / 700 MHz</li> <li>• 4G : TDD-LTE B38/B40/B41 - 2600 / 2300 / 2500 MHz</li> <li>• 3G : DC-HSPA+/HSPA/UMTS B1/B8 - 2100 / 900 MHz</li> </ul>  | ...   | ...             |
| LTE                           | ✓   | ...   | ...             |
| QSS                           | —   | ...   | ...             |
| WDS                           | —   | ...   | ...             |
| DHCP server                   | ✓   | ...   | ...             |
| Protections                   | <ul style="list-style-type: none"> <li>• WPA-PSK/WPA2-PSK</li> <li>• SSID hiding</li> <li>• MAC addresses filtering</li> </ul>  | ...   | ...             |
| Management interface          | Web browser   | ...   | ...             |
| Main features                 | <ul style="list-style-type: none"> <li>• SIM socket</li> <li>• ON/OFF button</li> <li>• WPS/RESET button</li> <li>• DHCP client/server support</li> <li>• DHCP client list</li> <li>• Static routing</li> <li>• Default address : 192.168.1.1</li> <li>• WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems</li> </ul> | <ul style="list-style-type: none"> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Control of color, color temperature, brightness, effect, allows any interior design</li> </ul> | ...             |
| Power supply                  | <ul style="list-style-type: none"> <li>• 12 V DC / 1 A (power adapter included)</li> <li>• 5 V / 2 A via micro USB port</li> </ul>  | ...   | ...             |
| Operation temp                | 0 °C ... 40 °C  | -20 °C ... 50 °C  | ...             |
| Permissible relative humidity | 10 % ... 90 % (non-condensing)  | ...   | ...             |
| Weight                        | 0.32 kg   | 0.030 kg  | 0.002 kg        |
| Dimensions                    | 200 x 145 x 49 mm   | 47 x 47 x 20 mm   | 140 x 15 x 5 mm |
| Manufacturer / Brand          | ALINK   | ZAMEL   | ORNO            |
| Guarantee                     | 2 years   | 2 years   | 2 years         |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00